Product End of Life Instructions

Smart-UPS Battery Systems

The APC Smart-UPS SRT Battery Pack products protect equipment and critical data from interruptions by supplying reliable, network-grade back up power reliably and efficiently to the APC Smart-UPS products.







A Potential disassembly risks

Batteries may contain an electrical charge, avoid creating short across terminals. Cracked or bloated batteries may be hazardous and represent a lead (Pb) exposure.

S End of Life Instructions



Recommendation	Number on drawing	Component / Material	Weight (in g)	Comment
To be depolluted	1	Printed Circuit Boards	1084	Mass is for PCBAs>10cm2 in surface area.
To be depolluted	2	Sealed Lead Acid Batteries	30400	See: Smart-UPS SRT 192V 5kVA and 6kVA Battery Pack for End of Life Instructions. See: material Safety Data sheet available at www.apc.com Use authorized battery recycler. Caution: Batteries may contain an electrical charge, avoid creating short across terminals. Caution:Cracked or bloated batteries may be hazardous and represent a lead (Pb) exposure. This unit is heavy. To lighten the unit, remove the batteries. Refer to unpacking instructions on the carton the unit is shipped.
To be dismantled	3	External Power Cables	16200	Power cables with the unit.

Product description

l I

Manufacturer identification	Schneider Electric Industries SAS	
Brand name	APC	
Product function	The Smart-UPS Battery Systems provides, additional back up power (time) to Smart-UPS for servers, voice / data networks, medical labs, and light industrial applications.	
Product reference	SRT192BP	
Additional similar product references	BR24BP(X), BX1500BP, DLRT192RM(X), FJRT192(X), HT(X), IBMR192RTBP3U(X), NM(X), RWRT192XLBP, SBATTBLK, SMX(X), SMV(X), SRC(X)LMP(X), SRT(X), SRV(X), SU(X), SUM(X), SURT(TDBATT, UXBP(X) where (X) are product sub-categories	
Total representative product mass	81562,42	
Representative product dimensions	432mm x 130mm x 682mm	
Accessories	None	
Date of information release	01/2019	

Additional information

Legal information	This product family is in the scope of European Union directive 2012/19/EU on Waste Electrical and Electronic Equipment (WEEE). The product family must be disposed according to the legislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product.		
In case of special transportation: transportation method	The battery pack used in this product range contains lead acid batteries that are regulated as Dangerous Goods shipping must be performed in accordance with the appropriate transportation regulations.		
Recyclability potential	48%	Based on "ECO'DEEE recyclability & recoverability calculation method" (version V1, 20 Sep 2008 presented to the French Agency for Environment and Energy Management: ADEME).	

Schneider Electric Industries SAS Customer Care Center www.schneider-electric.com/contact 35, rue Joseph Monier CS 30323 F- 92506 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 896 313 776 € www.schneider-electric.com

Published by Schneider Electric

 $\ensuremath{\mathbb{C}}$ 2018 - Schneider Electric – All rights reserved