



WADI-A cable gland

Presse étoupe WADI-A



OTHER APPLICATIONS

IP PROTECTION :
IP 68

OPERATING TEMPERATURE :
-25 °C / +120 °C

SPECIAL FEATURES :

- Variants configurations sealing
- Increased strain relief

MATERIAL :

- Nickel-plated brass, stainless steel
- 316L-1.4404-V4A on request
- Seal : TPE
- O-ring : nitrile
- Galvanized steel washer

THREAD :
Metric, PG

CERTIFICATION :
IEC 62 444

ACCESSORIES AVAILABLE :
See accessories page

INDICE DE PROTECTION :
IP 68

PLAGE DE TEMPÉRATURE :
-25 °C / +120 °C

AVANTAGES TECHNIQUES :

- Garnitures pour diverses configurations
- Résistance à la traction renforcée

MATIÈRE :

- Laiton nickelé, inox 316L-1.4404-V4A sur demande
- Garniture : TPE
- Joint torique : nitrile
- Rondelle : acier zingué


FILETAGE :
Métrique, PG

CERTIFICATION :
IEC 62 444


ACCESSOIRES DISPONIBLES :
Voir page des accessoires




WADI A TYPE 1




WADI A TYPE 2




WADI A TYPE 3



WADI A TYPE 4



WADI A TYPE 5



	Thread T	Type Number	Part Number	Overall cable diameter D		H1	H2	E	L	Packing
				Min	Max					
Metric	12	1	C3912000	2,0	3,0	14	14	7,0	16,0	50
	12	1	C3912001	4,0	6,5	14	14	7,0	16,0	50
	12	2	C3912002	4,0	7,0	14	14	7,0	16,0	50
	16	1	C3916000	5,0	7,0	17	17	7,0	17,5	50
	16	1	C3916001	6,0	8,0	17	17	7,0	17,5	50
	16	1	C3916002	7,0	10,0	17	17	7,0	17,5	50
	16	2	C3916003	7,0	10,0	17	17	7,0	17,5	50
	16	3	C3916010	5,0	12,0	20	20	7,0	17,5	50
	20	2	C3920000	6,5	10,5	24	24	7,0	22,0	50
	20	4	C3920001	8,0	12,0	24	24	7,0	22,0	50
	20	2	C3920002	10	15,0	24	24	7,0	22,0	50
	20	3	C3920003	7,0	15,0	24	24	7,0	22,0	50
	25	2	C3925000	6,5	10,5	27	24	8,0	21,0	20
	25	5	C3925002	3,5	15,0	27	24	8,0	21,0	20
	25	3	C3925003	7,0	15,0	27	24	8,0	21,0	20
	25	3	C3925010	12,0	20,5	32	32	8,0	25,0	20
	25	2	C3925011	16,0	20,5	32	32	8,0	25,0	20
	32	3	C3932000	16,0	26,0	38	38	8,5	30,5	20
	40	3	C3940000	24,0	35,0	50	50	8,5	27,5	20
	50	3	C3950000	35,0	45,0	58	58	9,5	30,5	10
63	3	C3963000	38,0	49,0	64	64	10,5	32,5	5	
PG	07	1	C2907109	2,0	3,0	14	14	6,0	16,0	50
	07	1	C2907000	4,0	6,5	14	14	6,0	16,0	50
	07	2	C2907200	4,0	7,0	14	14	6,0	16,0	50
	09	1	C2909004	5,0	7,0	17	17	6,5	17,5	50
	09	1	C2909103	6,0	8,0	17	17	6,5	17,5	50
	09	1	C2909202	7,0	9,0	17	17	6,5	17,5	50
	09	1	C2909203	7,0	10,0	17	17	6,5	17,5	50
	09	2	C2909300	7,0	10,0	17	17	6,5	17,5	50
	11	1	C2911007	5,0	7,0	20	17	6,0	14,0	50
	11	1	C2911106	6,0	8,0	20	17	6,0	14,0	50
	11	1	C2911205	7,0	10,0	20	17	6,0	14,0	50
	11	3	C2911304	5,0	12,0	20	20	6,0	14,0	50
	11	3	C2911403	7,0	15,0	24	24	6,5	13,5	50
	13	2	C2913400	6,5	10,5	24	24	6,5	21,5	50
	13	4	C2913001	8,0	12,0	24	24	6,5	21,5	50
	13	2	C2913300	10,0	15,0	24	24	6,5	21,5	50
	13	3	C2913100	7,0	15,0	24	24	6,5	21,5	50
	16	2	C2916200	6,5	10,5	24	24	6,5	21,5	50
	16	4	C2916002	8,0	12,0	24	24	6,5	21,5	50
	16	3	C2916101	7,0	15,0	24	24	6,5	21,5	50
21	3	C2921006	12,0	20,5	32	32	7,5	24,5	25	
21	2	C2921105	16,0	20,5	32	32	7,5	24,5	20	
21	2	C2921200	17,0	21,5	32	32	7,5	24,5	20	
29	3	C2929002	16,0	26,0	38	38	8,0	30,0	20	
36	3	C2936000	24,0	35,0	50	50	9,0	28,0	10	
42	3	C2942001	35,0	45,0	58	58	10,0	31,0	5	
48	3	C2949000	38,0	49,0	64	64	11,0	33,0	5	