

Round and hexagonal PLUGS

BOUCHONS ronds et 6 pans

ACCESSORIES

IP PROTECTION :

IP 65 (round) / IP 68 (hexagonal) without sealing

OPERATING TEMPERATURE :

- 30 °C / +120 °C (polyamide 6 glassfiber 25% reinforced)
- 40 °C / +135 °C (polycarbonate)
- 20 °C / +70 °C (polystyrene)

SPECIAL FEATURES :

- Can be assembled with a screwdriver
- Various possible uses (different materials, round, hexagonal)

Colors available :

- RAL 7035
- RAL 7001
- RAL 9005

MATERIAL :

- Polyamide 6 glassfiber 25 % reinforced (hexagonal & round metric)
- Polycarbonate (hexagonal PG)
- Polystyrene (round PG)
- Available stainless steel 316L-1.4404-V4A

THREAD :

Metric, PG

INDICE DE PROTECTION :

IP 65 (rond) / IP 68 (6 pans) sans joint

PLAGE DE TEMPÉRATURE :

- 30 °C / +120 °C (polyamide 6 chargé 25% fibre de verre)
- 40 °C / +135 °C (polycarbonate)
- 20 °C / +70 °C (polystyrène)

AVANTAGES TECHNIQUES :

- Montage possible avec un tournevis
- Différentes utilisations possibles (différentes matières, rond, 6 pans)

Couleurs disponibles :

- RAL 7035
- RAL 7001
- RAL 9005

MATIÈRE :

- Polyamide 6 chargé 25 % fibre de verre (6 pans & rond métrique)
- Polycarbonate (6 pans PG)
- Polystyrène (rond PG)
- Disponible en inox 316L-1.4404-V4A

FILETAGE :

Métrique, PG

HEXAGONAL PLUGS / BOUCHONS 6 PANS

	Thread T	Part Number		H	E	L	Packing
		RAL 7035	RAL 9005				
Metric	12	G4812210	G4812220	16	8,0	11,0	50
	16	G4816210	G4816220	20	8,0	12,0	50
	20	G4820210	G4820220	26	9,0	13,0	50
	25	G4825210	G4825220	32	10,0	15,0	20
	32	G4832210	G4832220	40	11,0	16,5	20
	40	G4840210	G4840220	48	12,0	18,0	20
	50	G4850210	G4850220	55	13,0	21,0	10
PG	63	G4863210	G4863220	70	15,0	24,5	5
	7	G4607007	H4607014	15	6,5	10,0	50
	9	G4609001	H4609018	19	7,0	10,5	50
	11	G4611004	H4611011	22	8,0	11,5	50
	13	G4613008	H4613015	24	9,0	12,5	50
	16	G4616009	H4616016	27	9,0	12,5	50
	21	G4621003	H4621010	32	10,0	14,5	25
	29	G4629009	H4629016	41	12,0	18,0	25
	36	G4636007	H4636014	55	14,0	21,5	10
	42	G4642008	H4642015	60	15,5	24,0	10
	48	G4649007	H4649014	65	16,0	26,0	5

ROUND PLUGS / BOUCHONS RONDS

	Thread T	Part Number			D	E	L	Packing
		RAL 7001	RAL 7035	RAL 9005				
Metric	12	G4512200	G4512210	G4512220	16	6,0	8,0	50
	16	G4516200	G4516210	G4516220	20	6,0	8,0	50
	20	G4520200	G4520210	G4520220	26	8,0	10,5	50
	25	G4525200	G4525210	G4525220	32	8,0	11,0	50
	32	G4532200	G4532210	G4532220	40	10,0	13,5	20
	40	G4540200	G4540210	G4540220	48	10,0	14,0	20
	50	G4550200	G4550210	G4550220	55	12,0	17,0	10
	63	G4563200	G4563210	G4563220	70	12,0	18,0	5

