

# DATENBLATT

## USB2.0 Anschlusskabel A-B, St.-St., 3,0m, schwarz, Premium



### Beschreibung

Unterstützt Datenübertragungsraten bis zu 480 Mbit/s. Leitermaterial: Kupfer. Leiteraufbau: AWG28 / AWG20. Schirmung: Folie + 80% Geflechschirm. Umspritzte Stecker, PVC Mantel.

### Allgemeine Daten

Anzahl der Pole Anschluss 1	4
Anzahl der Pole Anschluss 2	4

### Cable construction

Ausführung Anschluss 2	Stecker
Ausführung Anschluss 1	Stecker

### Kabelaufbau

Steckverbindertyp Anschluss 2	USB-B
Steckverbindertyp Anschluss 1	USB-A

### Verfügbare Varianten

Dieses Datenblatt wurde maschinell am 24-02-2025 erzeugt. Technische Änderungen vorbehalten.



# DATENBLATT

## USB2.0 Anschlusskabel A-B, St.-St., 3,0m, schwarz, Premium

ArtNr.	Bezeichnung	Farbe	Länge
K5256SW.0,5	USB2.0 Anschlusskabel A-B, St.-St., 0,5m, schwarz, Premium	schwarz	0,5 m
K5256SW.1	USB2.0 Anschlusskabel A-B, St.-St., 1,0m, schwarz, Premium	schwarz	1,0 m
K5256SW.1,5	USB2.0 Anschlusskabel A-B, St.-St., 1,5m, schwarz, Premium	schwarz	1,5 m
K5256SW.1,8	USB2.0 Anschlusskabel A-B, St.-St., 1,8m, schwarz, Premium	schwarz	1,8 m
K5256SW.3	USB2.0 Anschlusskabel A-B, St.-St., 3,0m, schwarz, Premium	schwarz	3,0 m
K5256SW.5	USB2.0 Anschlusskabel A-B, St.-St., 5,0m, schwarz, Premium	schwarz	5,0 m

### Zeichnungen

Dieses Datenblatt wurde maschinell am 24-02-2025 erzeugt. Technische Änderungen vorbehalten.



# DATENBLATT

## USB2.0 Anschlusskabel A-B, St.-St., 3,0m, schwarz, Premium

P1: M-942A	P2: M-945A																																																	
			<p>Customer No: No.6</p>																																															
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>ITEM NO.</th> <th>LENGTH(L)</th> </tr> <tr> <td>K5256SW.0.22</td> <td>220mm</td> </tr> <tr> <td>K5256SW.0.5</td> <td>500mm</td> </tr> <tr> <td>K5256SW.1</td> <td>1000mm</td> </tr> <tr> <td>K5256SW.1.8</td> <td>1800mm</td> </tr> <tr> <td>K5256SW.3</td> <td>3000mm</td> </tr> <tr> <td>K5256SW.5</td> <td>5000mm</td> </tr> <tr> <td>K5256SW.2</td> <td>2000mm</td> </tr> <tr> <td>K5256SW.2.2</td> <td>2200mm</td> </tr> <tr> <td>K5256SW.1.5</td> <td>1500mm</td> </tr> <tr> <td>K5256SW.4.5</td> <td>4500mm</td> </tr> </table>			ITEM NO.	LENGTH(L)	K5256SW.0.22	220mm	K5256SW.0.5	500mm	K5256SW.1	1000mm	K5256SW.1.8	1800mm	K5256SW.3	3000mm	K5256SW.5	5000mm	K5256SW.2	2000mm	K5256SW.2.2	2200mm	K5256SW.1.5	1500mm	K5256SW.4.5	4500mm	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">9768-7</td> </tr> <tr> <td style="width:50%;">P1</td> <td style="width:50%;">P2</td> </tr> <tr> <td>1</td> <td>1</td> </tr> <tr> <td>2</td> <td>2</td> </tr> <tr> <td>3</td> <td>3</td> </tr> <tr> <td>4</td> <td>4</td> </tr> <tr> <td>SHIELD</td> <td>SHIELD</td> </tr> <tr> <td></td> <td style="text-align: center;">20#</td> </tr> </table>			9768-7		P1	P2	1	1	2	2	3	3	4	4	SHIELD	SHIELD		20#							
ITEM NO.	LENGTH(L)																																																	
K5256SW.0.22	220mm																																																	
K5256SW.0.5	500mm																																																	
K5256SW.1	1000mm																																																	
K5256SW.1.8	1800mm																																																	
K5256SW.3	3000mm																																																	
K5256SW.5	5000mm																																																	
K5256SW.2	2000mm																																																	
K5256SW.2.2	2200mm																																																	
K5256SW.1.5	1500mm																																																	
K5256SW.4.5	4500mm																																																	
9768-7																																																		
P1	P2																																																	
1	1																																																	
2	2																																																	
3	3																																																	
4	4																																																	
SHIELD	SHIELD																																																	
	20#																																																	
<p>REVISIONS HISTORY:</p> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>REV.</th> <th>DATE</th> <th>DESCRIPTION</th> </tr> <tr> <td>REV.1</td> <td>2008.4.10</td> <td>MOOPLY LENGTH FOR 2M TO 1.8M</td> </tr> <tr> <td>REV.2</td> <td>2008.4.10</td> <td>MOOPLY LENGTH FOR 2M TO 1.8M</td> </tr> <tr> <td>REV.3</td> <td>2009.3.19</td> <td>ADD LENGTH 0.5M AND THIS CABLE IS SILICONE FREE</td> </tr> <tr> <td>REV.4</td> <td>2009.5.21</td> <td>ADD Operating temperature&amp;Storage temperature</td> </tr> <tr> <td>REV.5</td> <td>2013.1.23</td> <td>ADD Operating temperature&amp;Storage temperature</td> </tr> <tr> <td>REV.6</td> <td>2013.1.30</td> <td>ADD CABLE AND MOLDED PVC COLD-RESISTANT TEMPERATURE</td> </tr> <tr> <td>REV.7</td> <td>2013.11.05</td> <td>TAKE OFF LENGTH 2M</td> </tr> <tr> <td>REV.8</td> <td>2015.2.04</td> <td>MODIFY DRAWING &amp; LENGTH</td> </tr> <tr> <td>REV.9</td> <td>2015.05.27</td> <td>ADD LENGTH 10M</td> </tr> <tr> <td>REV.10</td> <td>2015.09.15</td> <td>MODIFY LETTERING</td> </tr> <tr> <td>REV.11</td> <td>2016.12.19</td> <td>ADD LENGTH 0.22M</td> </tr> <tr> <td>REV.12</td> <td>2017.04.11</td> <td>ADD LENGTH 4.5M AND ITEM NO.K5256SW.4.5</td> </tr> <tr> <td>REV.13</td> <td>2017.10.13</td> <td>ADD LENGTH 2.2M AND ITEM NO.K5256SW.2.2</td> </tr> <tr> <td>REV.14</td> <td>2017.12.15</td> <td>TAKE OFF LENGTH 10M</td> </tr> </table>			REV.	DATE	DESCRIPTION	REV.1	2008.4.10	MOOPLY LENGTH FOR 2M TO 1.8M	REV.2	2008.4.10	MOOPLY LENGTH FOR 2M TO 1.8M	REV.3	2009.3.19	ADD LENGTH 0.5M AND THIS CABLE IS SILICONE FREE	REV.4	2009.5.21	ADD Operating temperature&Storage temperature	REV.5	2013.1.23	ADD Operating temperature&Storage temperature	REV.6	2013.1.30	ADD CABLE AND MOLDED PVC COLD-RESISTANT TEMPERATURE	REV.7	2013.11.05	TAKE OFF LENGTH 2M	REV.8	2015.2.04	MODIFY DRAWING & LENGTH	REV.9	2015.05.27	ADD LENGTH 10M	REV.10	2015.09.15	MODIFY LETTERING	REV.11	2016.12.19	ADD LENGTH 0.22M	REV.12	2017.04.11	ADD LENGTH 4.5M AND ITEM NO.K5256SW.4.5	REV.13	2017.10.13	ADD LENGTH 2.2M AND ITEM NO.K5256SW.2.2	REV.14	2017.12.15	TAKE OFF LENGTH 10M	<p>MARKING:</p> <p>H-SPEED USB Revision 2.0 SHIELDED 28AWG/1PR+20AWG/2C VW-1 80°C 30V</p> <p>The cable must accord:</p> <p>Operating temperature: between -20°C and +80°C</p> <p>Storage temperature: between -40°C and +85°C</p> <p>* NOTE: All relevant materials are complied with RoHS directive.</p> <p>100% SHORT AND PEN TEST</p>		
REV.	DATE	DESCRIPTION																																																
REV.1	2008.4.10	MOOPLY LENGTH FOR 2M TO 1.8M																																																
REV.2	2008.4.10	MOOPLY LENGTH FOR 2M TO 1.8M																																																
REV.3	2009.3.19	ADD LENGTH 0.5M AND THIS CABLE IS SILICONE FREE																																																
REV.4	2009.5.21	ADD Operating temperature&Storage temperature																																																
REV.5	2013.1.23	ADD Operating temperature&Storage temperature																																																
REV.6	2013.1.30	ADD CABLE AND MOLDED PVC COLD-RESISTANT TEMPERATURE																																																
REV.7	2013.11.05	TAKE OFF LENGTH 2M																																																
REV.8	2015.2.04	MODIFY DRAWING & LENGTH																																																
REV.9	2015.05.27	ADD LENGTH 10M																																																
REV.10	2015.09.15	MODIFY LETTERING																																																
REV.11	2016.12.19	ADD LENGTH 0.22M																																																
REV.12	2017.04.11	ADD LENGTH 4.5M AND ITEM NO.K5256SW.4.5																																																
REV.13	2017.10.13	ADD LENGTH 2.2M AND ITEM NO.K5256SW.2.2																																																
REV.14	2017.12.15	TAKE OFF LENGTH 10M																																																
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>No.</th> <th>DESCRIPTION</th> <th>QTY</th> <th>Supplier</th> </tr> <tr> <td>1</td> <td>USB A MALE 20 GOLD PLATING 30V ON CONTACT, WHITE INSULATION, THREE RES SOLDER FREE</td> <td>1set</td> <td>M108</td> </tr> <tr> <td>2</td> <td>USB B MALE 20 GOLD PLATING 30V ON CONTACT, WHITE INSULATION, THREE RES SOLDER FREE</td> <td>1set</td> <td>M108</td> </tr> <tr> <td>3</td> <td>USB 2.0 CABLE "UL STYLE" 1 TWISTED PAIR 28AWG AND 2C 20AWG BRND 09M</td> <td>1-20mm</td> <td>M304</td> </tr> <tr> <td>4</td> <td>MOLDED PVC BLACK (-40°C/+85°C,COLD-RESISTANT)</td> <td>HHB10-030W09</td> <td>M304</td> </tr> <tr> <td>5</td> <td>MOLDED PVC BLACK (-40°C/+85°C,COLD-RESISTANT)</td> <td>HHB10-030W09</td> <td>M304</td> </tr> </table>			No.	DESCRIPTION	QTY	Supplier	1	USB A MALE 20 GOLD PLATING 30V ON CONTACT, WHITE INSULATION, THREE RES SOLDER FREE	1set	M108	2	USB B MALE 20 GOLD PLATING 30V ON CONTACT, WHITE INSULATION, THREE RES SOLDER FREE	1set	M108	3	USB 2.0 CABLE "UL STYLE" 1 TWISTED PAIR 28AWG AND 2C 20AWG BRND 09M	1-20mm	M304	4	MOLDED PVC BLACK (-40°C/+85°C,COLD-RESISTANT)	HHB10-030W09	M304	5	MOLDED PVC BLACK (-40°C/+85°C,COLD-RESISTANT)	HHB10-030W09	M304	<p>PART NO. 9768-7</p> <p>Revision:</p>																							
No.	DESCRIPTION	QTY	Supplier																																															
1	USB A MALE 20 GOLD PLATING 30V ON CONTACT, WHITE INSULATION, THREE RES SOLDER FREE	1set	M108																																															
2	USB B MALE 20 GOLD PLATING 30V ON CONTACT, WHITE INSULATION, THREE RES SOLDER FREE	1set	M108																																															
3	USB 2.0 CABLE "UL STYLE" 1 TWISTED PAIR 28AWG AND 2C 20AWG BRND 09M	1-20mm	M304																																															
4	MOLDED PVC BLACK (-40°C/+85°C,COLD-RESISTANT)	HHB10-030W09	M304																																															
5	MOLDED PVC BLACK (-40°C/+85°C,COLD-RESISTANT)	HHB10-030W09	M304																																															
<p>APPROVED</p> <p>CHECKED HU</p> <p>DRAWING JIANGJU</p>			<p>DATE 15/DEC/17</p> <p>ITEM NO. K5256SW.X</p>																																															
			<p>UNIT:mm</p>																																															

Dieses Datenblatt wurde maschinell am 24-02-2025 erzeugt. Technische Änderungen vorbehalten.

