



profiled light with t-slot backsided

<b>Product-Nr.</b>	150914-04
<b>EAN:</b>	4260556625393
<b>Model:</b>	PROFILED AC
Order number:	150914-04
<b>Model:</b>	PROFILED AC
Type:	profiled light with t-slot backsided
<b>Illuminant:</b>	SMD LED
Total output incl. driver:	~41 W
<b>Power consumption:</b>	~37 W
Lamp luminous flux:	5678 lm
<b>Lamp luminous efficiency:</b>	~155 lm/W
Light distribution:	direct
<b>Light colour:</b>	5600K 3-step MacAdam
Connected load:	90-305V AC ± 10%, 50-60 Hz
<b>Power supply:</b>	inbuilt
Connection (connector):	connection cable with power plug
<b>Degree of protection:</b>	IP40
Class of protection:	I
<b>Glare control:</b>	Microprisms
Beam angle (optics):	100°
<b>Operating temperature:</b>	-10 °C -> +45 °C (14 °F -> 113 °F)
Colour rendering (Ra):	>85
<b>Lamps lifetime:</b>	> 100.000h (L80/B10)
Housing material:	aluminium
<b>Cover material:</b>	plastics
Height [B] x Width [C]:	65 mm x 45 mm (~2,56" x ~1,77")
<b>Length [A]:</b>	1500 mm (~59,06")
Weight (net):	3200 g (~113 oz)
<b>Gross weight:</b>	3900 g (~138 oz)
Risk group (DIN EN 62471):	free group
<b>Markings:</b>	CE, UKCA
Mounting accessories:	optional
<b>Made in:</b>	Germany
Feature:	universal light, dimmable