



LED surface-mounted light



Product-Nr.	154690-01
EAN:	4260556626598
Model:	TUBELED_25 RGB-W
Order number:	154690-01
Model:	TUBELED_25 RGB-W
Type:	LED surface-mounted light
Illuminant:	SMD RGB-W Cluster LED
Power consumption white:	~28,8 W
White lamp luminous flux:	4600 lm
Power consumption RED:	~8,64 W
Lamp luminous flux RED:	552 lm
Power consumption GREEN:	~5,76 W
Lamp luminous flux GREEN:	1008 lm
Power consumption BLUE:	~8,64 W
Lamp luminous flux BLUE:	336 lm
Light colour white:	5000K 3-step MacAdam
Colour rendering WHITE (Ra):	>85
Number of poles:	5
Connected load:	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector):	M8 B-coded
Degree of protection:	IP67
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-30 °C - +55 °C (-22 °F - 131 °F)
Lamps lifetime:	> 100,000 h (L80/B10)
Vibration resistance:	at 10 to 55 Hz (amplitude 0.35 mm (~0,01"))
Shock resistance:	up to 50 g (~2 oz)
Housing material:	aluminium
Cover material:	tempered glass, shatterproof
Height [B] x Width [C]:	~23 mm x ~28 mm (~0,91" x ~1,1")
Length [A]:	1040 mm (~40,94")
Weight (net):	700 g (~25 oz)
Gross weight:	1100 g (~39 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Mounting accessories:	Optional
Made in:	Germany
Feature:	RGB-W: Illumination and beacon in one light; connection