

LED system light



Product-Nr. 155410-01

EAN:

Model: SYSTEMLED EVO - POWER Tageslichtweiss

Order number: 155410-01

Model: SYSTEMLED EVO - POWER Tageslichtweiss

Type: LED system light

Illuminant: SMD LED

Total output incl. driver: ~80 W

Power consumption: ~73 W

Lamp luminous flux: 13000 lm

Lamp luminous efficiency: 184 lm/W

Light distribution: direct

Light colour: 5700K 3-step MacAdam

Connected load: 120-277VAC, 50 - 60 Hz

Power supply: integrated

Connection (connector): Wieland GST18

Degree of protection: IP40

Class of protection: I

Glare control: Microprisms

Beam angle (optics): 90°

Operating temperature: -10 °C -> +50 °C (14 °F -> 122 °F)

Colour rendering (Ra): >90 (typ. 95)

Lamps lifetime: > 100.000h (L80/B10)

Housing material: Aluminium, PMMA

Height [B] x Width [C]: 48 mm x 139 mm (~1,89" x ~5,47")

Length [A]: 1782 mm (~70,16")

Mounting: T-slot rear (8 mm)

Risk group (DIN EN 62471): free group


Markings: CE, UKCA

Dimmable: yes

Mounting accessories: optional

Made in: Germany

Feature: externally dimmable/switchable



Abstand d=100 cm
 $E_{min} = 2774 \text{ lux}$
 $E_{max} = 3397 \text{ lux}$
 $E_{avg} = 1926 \text{ lux}$

