




## LED system light



|                            |                                   |
|----------------------------|-----------------------------------|
| Product-Nr.                | 155420-02                         |
| EAN:                       | 4260556627656                     |
| Model:                     | SYSTEMLED EVO - ECO Neutral White |
| Order number:              | 155420-02                         |
| Model:                     | SYSTEMLED EVO - ECO Neutral White |
| Type:                      | LED system light                  |
| Illuminant:                | SMD LED                           |
| Total output incl. driver: | ~51 W                             |
| Power consumption:         | ~46 W                             |
| Lamp luminous flux:        | 7960 lm                           |
| Lamp luminous efficiency:  | 173 lm/W                          |
| Light distribution:        | Direct                            |
| Light colour:              | 4000K 3-step MacAdam              |
| R9:                        | 90                                |
| Colour rendering (Ra):     | >90 (typ. 95)                     |
| UGR:                       | <22                               |
| Connected load:            | 120-277V AC $\pm$ 10%, 50-60 Hz   |
| Power supply:              | Integrated                        |
| Connection (connector):    | Wieland GST18                     |
| Degree of protection:      | IP40                              |
| Class of protection:       | I                                 |
| Glare control:             | Microprisms                       |
| Beam angle (optics):       | 90°                               |
| Operating temperature:     | -10 °C - +50 °C (14 °F - 122 °F)  |
| Storage temperature:       | -20 °C - +80 °C (-4 °F - 176 °F)  |
| Lamps lifetime:            | > 100,000 h (L80/B10)             |
| Housing material:          | aluminum and PMMA                 |
| Height [B] x Width [C]:    | 48 mm x 139 mm (~1,89" x ~5,47")  |
| Length [A]:                | 1782 mm (~70,16")                 |
| Mounting:                  | T-slot rear (8 mm)                |
| Weight (net):              | 4700 g (~166 oz)                  |
| Gross weight:              | 6580 g (~232 oz)                  |
| Risk group (DIN EN 62471): | Free group                        |
| Markings:                  | CE, UKCA                          |
| Dimmable:                  | Optional via accessories          |
| Mounting accessories:      | Optional                          |
| Made in:                   | Germany                           |