


LED tube luminaire



Product-Nr.	110110-02
EAN:	4260556624945
Model:	INROLED_50 Ecolab DC ECO
Order number:	110110-02
Model:	INROLED_50 Ecolab DC ECO
Type:	LED tube luminaire
Illuminant:	SMD LED
Power consumption:	~13 W
Lamp luminous flux:	2004 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-30 °C -> +65 °C (-22 °F -> 149 °F) (briefly +70 °C (158 °F))
Colour rendering (Ra):	>85
Lamps lifetime:	> 100.000h (L80/B10)
Cover material:	polycarbonate, milky, shatterproof with Ecolab coating
impact resistance:	IK09
Height [B] x Width [C]:	Ø 50 mm (~1,97")
Length [A]:	565 mm (~22,24")
Weight (net):	950 g (~34 oz)
Gross weight:	1150 g (~41 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	optional via accessories
Mounting accessories:	incl. luminaire holder made of metal detectable PP
Made in:	Germany
Feature:	Food+Beverage suitable: Ecolab certified, HACCP certificate