



LED system light and workplace lighting



| | |
|-----------------------------------|--|
| Product-Nr. | 110914-12 |
| EAN: | 4260556620329 |
| Model: | UNILED SL DC |
| Order number: | 110914-12 |
| Model: | UNILED SL DC |
| Type: | LED system light and workplace lighting |
| Illuminant: | SMD LED |
| Power consumption: | ~24 W |
| Lamp luminous flux: | 3798 lm |
| Lamp luminous efficiency: | ~155 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 24V DC \pm 10% |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP50 |
| Class of protection: | III |
| Glare control: | opal white |
| Beam angle (optics): | 100° |
| Operating temperature: | -10 °C -> +60 °C (14 °F -> 140 °F) |
| Colour rendering (Ra): | >85 |
| Lamps lifetime: | > 60.000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | plastic soft |
| Height [B] x Width [C]: | 35 mm x 85 mm (~1,38" x ~3,35") |
| Length [A]: | 545 mm (~21,46") |
| Weight (net): | 850 g (~30 oz) |
| Gross weight: | 1300 g (~46 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | optional via accessories |
| Mounting accessories: | optional |
| Made in: | Germany |
| Feature: | homogeneous lighting, shadow- and glare-free |