

LED surface-mounted luminaire



| | |
|-----------------------------------|---|
| Product-Nr. | 111010-06 |
| EAN: | 4260556624051 |
| Model: | LEANLED II klar |
| Order number: | 111010-06 |
| Model: | LEANLED II klar |
| Type: | LED surface-mounted luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~24 W |
| Lamp luminous flux: | 4008 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light distribution: | direct |
| Light colour: | 5600K 3-step MacAdam |
| Connected load: | 24V DC ± 10% |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP54 |
| Class of protection: | III |
| Beam angle (optics): | 120° |
| Operating temperature: | -10 °C -> +60 °C (14 °F -> 140 °F) |
| Colour rendering (Ra): | >85 |
| Lamps lifetime: | > 100.000h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | Polycarbonat, clear, shatterproof |
| Height [B] x Width [C]: | 31 mm x 26 mm (~1,22" x ~1,02") |
| Length [A]: | 1020 mm (~40,16") |
| Weight (net): | 700 g (~25 oz) |
| Gross weight: | 1000 g (~35 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | optional via accessories |
| Mounting accessories: | 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope |
| Made in: | Germany |

