## LED surface-mounted luminaire

| | |
|---|---|
| **Product-Nr.** | 111010-26 |
| **EAN:** | 4260556624198 |
| **Model:** | LEANLED II Clear Cascadeable |










| | |
|---|---|
| Order number: | 111010-26 |
| Model: | LEANLED II Clear Cascadeable |
| Type: | LED surface-mounted luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~24 W |
| Lamp luminous flux: | 4008 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light distribution: | Direct |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >85 |
| Connected load: | 24V DC ± 10% |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP54 |
| Class of protection: | III |
| Beam angle (optics): | 120° |
| Operating temperature: | -10 °C - +60 °C (14 °F - 140 °F) |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | Polycarbonat, clear, shatterproof |
| Height [B] x Width [C]: | 31 mm x 26 mm (~1,22“ x ~1,02“) |
| Length [A]: | 1020 mm (~40,16“) |
| Weight (net): | 780 g (~28 oz) |
| Gross weight: | 900 g (~32 oz) |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529), D mark |
| Dimmable: | Optional via accessories |
| Mounting accessories: | 2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope |
| Made in: | Germany |
| Feature: | cascadable, several luminiares can be interlinked electrically. The entiere power consuption may not exceed 4A DC. |
| cascadable: | yes |



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com