

LED surface-mounted luminaire



Product-Nr.	111010-31
EAN:	4260556624211
Model:	LEANLED II opalweiß kaskadierbar

Order number:	111010-31
Model:	LEANLED II opalweiß kaskadierbar
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED

Power consumption:	~4 W
Lamp luminous flux:	668 lm
Lamp luminous efficiency:	155 lm/W

Light distribution:	direct
Light colour:	5600K 3-step MacAdam

Connected load:	24V DC ± 10%
Connection (connector):	M12 A-coded

Degree of protection:	IP54
Class of protection:	III

Glare control:	opal white
-----------------------	------------

Beam angle (optics):	120°
-----------------------------	------

Operating temperature:	-10 °C -> +60 °C (14 °F -> 140 °F)
-------------------------------	------------------------------------

Colour rendering (Ra):	>85
-------------------------------	-----

Lamps lifetime:	> 100.000h (L80/B10)
------------------------	----------------------

Housing material:	aluminium
--------------------------	-----------

Cover material:	polycarbonate, soft
------------------------	---------------------

Height [B] x Width [C]:	31 mm x 26 mm (~1,22" x ~1,02")
--------------------------------	---------------------------------

Length [A]:	180 mm (~7,09")
--------------------	-----------------

Weight (net):	180 g (~6 oz)
----------------------	---------------

Gross weight:	330 g (~12 oz)
----------------------	----------------

Risk group (DIN EN 62471):	free group
-----------------------------------	------------

Markings:	CE, UKCA, ETL Listed (5003529)
------------------	--------------------------------

Dimmable:	optional via accessories
------------------	--------------------------

Mounting accessories:	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
------------------------------	---

Made in:	Germany
-----------------	---------

Feature:	cascadable, several luminaires can be interlinked electrically.
-----------------	---

cascadable:	yes
--------------------	-----

