

LED surface-mounted luminaire



Product-Nr. 111010-36

EAN: 4260556624266

Model: LEANLED II opalweiß kaskadierbar

Order number: 111010-36

Model: LEANLED II opalweiß kaskadierbar

Type: LED surface-mounted luminaire

Illuminant: SMD LED

Power consumption: ~24 W

Lamp luminous flux: 4008 lm

Lamp luminous efficiency: 155 lm/W

Light distribution: direct

Light colour: 5600K 3-step MacAdam

Connected load: 24V DC ± 10%

Connection (connector): M12 A-coded

Degree of protection: IP54

Class of protection: III

Glare control: opal white

Beam angle (optics): 120°

Operating temperature: -10 °C -> +60 °C (14 °F -> 140 °F)

Colour rendering (Ra): >85

Lamps lifetime: > 100.000h (L80/B10)

Housing material: aluminium

Cover material: Polycarbonate, soft

Height [B] x Width [C]: 31 mm x 26 mm (~1,22" x ~1,02")

Length [A]: 1020 mm (~40,16")

Weight (net): 700 g (~25 oz)

Gross weight: 1000 g (~35 oz)

Risk group (DIN EN 62471): free group

Markings: CE, UKCA, ETL Listed (5003529)

Dimmable: optional via accessories

Mounting accessories: 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope

Made in: Germany

Feature: cascadable, several luminaires can be interlinked electrically.

cascadable: yes

