


## LED surface mounted tube luminaire



|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| <b>Product-Nr.</b>                | 115210-02                                          |
| <b>EAN:</b>                       | 4260556621739                                      |
| <b>Model:</b>                     | INROLED_70 with Borosilicate Glass Protective Tube |
| Order number:                     | 115210-02                                          |
| <b>Model:</b>                     | INROLED_70 with Borosilicate Glass Protective Tube |
| <b>Type:</b>                      | LED surface mounted tube luminaire                 |
| <b>Illuminant:</b>                | SMD LED                                            |
| <b>Total output incl. driver:</b> | ~15 W                                              |
| <b>Power consumption:</b>         | ~13 W                                              |
| <b>Lamp luminous flux:</b>        | 2004 lm                                            |
| <b>Lamp luminous efficiency:</b>  | ~155 lm/W                                          |
| <b>Light distribution:</b>        | Direct                                             |
| <b>Light colour:</b>              | 5700K 3-step MacAdam                               |
| <b>Colour rendering (Ra):</b>     | >85                                                |
| <b>Connected load:</b>            | 90-305V AC $\pm$ 10%, 50-60 Hz                     |
| <b>Power supply:</b>              | Integrated                                         |
| <b>Connection (connector):</b>    | Cable entry, internal clamp                        |
| <b>Degree of protection:</b>      | IP67/IP69K                                         |
| <b>Class of protection:</b>       | I                                                  |
| <b>Glare control:</b>             | Microprisms                                        |
| <b>Beam angle (optics):</b>       | 125°                                               |
| <b>Operating temperature:</b>     | -10 °C - +40 °C (14 °F - 104 °F)                   |
| <b>Lamps lifetime:</b>            | > 100,000 h (L80/B10)                              |
| <b>Housing material:</b>          | aluminium inside                                   |
| <b>Cover material:</b>            | tempered glass, shatterproof                       |
| <b>Height [B] x Width [C]:</b>    | Ø 70 mm (~2,76")                                   |
| <b>Length [A]:</b>                | 650 mm (~25,59")                                   |
| <b>Weight (net):</b>              | 1450 g (~51 oz)                                    |
| <b>Gross weight:</b>              | 2000 g (~71 oz)                                    |
| <b>Risk group (DIN EN 62471):</b> | Free group                                         |
| <b>Markings:</b>                  | CE, UKCA                                           |
| <b>Mounting accessories:</b>      | Optional                                           |
| <b>Made in:</b>                   | Germany                                            |
| <b>Feature:</b>                   | cascadable                                         |
| <b>cascadable:</b>                | yes                                                |