

## LED surface mounted tube luminaire



<b>Product-Nr.</b>	115310-03
<b>EAN:</b>	4260556624761
<b>Model:</b>	INROLED_70 mit PC Schutzrohr
Order number:	115310-03
<b>Model:</b>	INROLED_70 mit PC Schutzrohr
<b>Type:</b>	LED surface mounted tube luminaire
<b>Illuminant:</b>	SMD LED
<b>Power consumption:</b>	~21 W
<b>Lamp luminous flux:</b>	3340 lm
<b>Lamp luminous efficiency:</b>	~155 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	5600K 3-step MacAdam
<b>Connected load:</b>	24V DC $\pm$ 10%
<b>Connection (connector):</b>	Cable entry, internal clamp
<b>Degree of protection:</b>	IP67/IP69K
<b>Class of protection:</b>	III
<b>Glare control:</b>	opal white
<b>Beam angle (optics):</b>	125°
<b>Operating temperature:</b>	-10 °C -> +45 °C (14 °F -> 113 °F)
<b>Colour rendering (Ra):</b>	>85
<b>Lamps lifetime:</b>	> 100.000h (L80/B10)
<b>Housing material:</b>	aluminium inside
<b>Cover material:</b>	polycarbonate, shatterproof
<b>Height [B] x Width [C]:</b>	Ø 70 mm (~2,76")
<b>Length [A]:</b>	921 mm (~36,26")
<b>Weight (net):</b>	2000 g (~71 oz)
<b>Gross weight:</b>	2950 g (~104 oz)
<b>Risk group (DIN EN 62471):</b>	free group
<b>Markings:</b>	CE, UKCA
<b>Dimmable:</b>	optional via accessories
<b>Mounting accessories:</b>	optional
<b>Made in:</b>	Germany
<b>Feature:</b>	cascadable (max. 4.0 A)
<b>cascadable:</b>	yes