

LED surface mounted tube luminaire



Product-Nr.	115410-01
EAN:	4260556621708
Model:	INROLED_70 mit Borosilikatglas-Schutzrohr

Order number:	115410-01
Model:	INROLED_70 mit Borosilikatglas-Schutzrohr

Type:	LED surface mounted tube luminaire
Illuminant:	SMD LED

Power consumption:	~28 W
Lamp luminous flux:	4342 lm

Lamp luminous efficiency:	~155 lm/W
---------------------------	-----------

Light distribution:	direct
Light colour:	5600K 3-step MacAdam

Connected load:	24V DC \pm 10%
Connection (connector):	Cable entry, internal clamp

Degree of protection:	IP67/IP69K
-----------------------	------------

Class of protection:	III
Glare control:	Microprisms

Beam angle (optics):	125°
Operating temperature:	-10 °C -> +45 °C (14 °F -> 113 °F)

Colour rendering (Ra):	>85
Lamps lifetime:	> 100.000h (L80/B10)

Housing material:	aluminium inside
Cover material:	safety glass, shatterproof

Height [B] x Width [C]:	Ø 70 mm (~2,76")
-------------------------	------------------

Length [A]:	1214 mm (~47,8")
-------------	------------------

Weight (net):	3950 g (~139 oz)
---------------	------------------

Gross weight:	5250 g (~185 oz)
---------------	------------------

Risk group (DIN EN 62471):	free group
----------------------------	------------

Markings:	CE, UKCA, ETL Listed (5003529)
-----------	--------------------------------

Dimmable:	optional via accessories
-----------	--------------------------

Mounting accessories:	optional
-----------------------	----------

Made in:	Germany
----------	---------

Feature:	cascadable (max. 4.0 A)
----------	-------------------------

cascadable:	yes
-------------	-----

