



LED surface-mounted luminaire for machines



Product-Nr.	118110-04
EAN:	4260556622958
Model:	TUBELED_40 II M40x1.5
Order number:	118110-04
Model:	TUBELED_40 II M40x1.5
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	~6 W
Lamp luminous flux:	1000 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Light Forming Technology
Light colour:	5600K 3-step MacAdam
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-30 °C -> +70 °C (-22 °F -> 158 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 100.000h (L80/B10)
Housing material:	aluminium
Cover material:	safety glass, 4 mm (0,16")
Height [B] x Width [C]:	29 mm x 40 mm (~1,14" x ~1,57") + \varnothing 70 mm (~2,76")
Length [A]:	309 mm (~12,17")
Weight (net):	550 g (~19 oz)
Gross weight:	900 g (~32 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003526), D mark
Dimmable:	optional via accessories
Mounting accessories:	Befestigung über M40x1.5
Made in:	Germany
Feature:	resistant to high temperatures, mounting in >40 mm hole at