



## LED surface-mounted luminaire

<b>Product-Nr.</b>	119510-03
<b>EAN:</b>	4260556624440
<b>Model:</b>	TUBELED_40 Element AC

Order number:	119510-03
<b>Model:</b>	TUBELED_40 Element AC
<b>Type:</b>	LED surface-mounted luminaire
<b>Illuminant:</b>	SMD LED
<b>Total output incl. driver:</b>	~34 W
<b>Power consumption:</b>	~34 W
<b>Lamp luminous flux:</b>	5120 lm
<b>Lamp luminous efficiency:</b>	127 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	daylight white (5200 - 5700K)
<b>Connected load:</b>	220-240V AC $\pm$ 10%, 50-60 Hz
<b>Connection (connector):</b>	M12 S-coded
<b>Degree of protection:</b>	IP54
<b>Class of protection:</b>	I
<b>Glare control:</b>	diffuser sheet for scattered light, PMMA
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-30 °C -> +50 °C (-22 °F -> 122 °F)
<b>Colour rendering (Ra):</b>	>80
<b>Lamps lifetime:</b>	> 100.000h (L80/B10)
<b>Housing material:</b>	aluminium, endcaps made of plastics
<b>Cover material:</b>	PMMA, frosted
<b>Height [B] x Width [C]:</b>	29 mm x 40 mm (~1,14" x ~1,57")
<b>Length [A]:</b>	1040 mm (~40,94")
<b>Weight (net):</b>	1290 g (~46 oz)
<b>Gross weight:</b>	1650 g (~58 oz)
<b>Risk group (DIN EN 62471):</b>	free group
<b>Markings:</b>	CE, UKCA, D mark
<b>Mounting accessories:</b>	optional
<b>Made in:</b>	Germany
<b>Feature:</b>	220-240V AC Anschluss, temperaturbeständig

