



LED adjustable arm light

Product-Nr.	120610-02
EAN:	4260556620268
Model:	UNILED II Articulated Arm
Order number:	120610-02
Model:	UNILED II Articulated Arm
Type:	LED adjustable arm light
Illuminant:	SMD LED
Power consumption:	~12 W
Lamp luminous flux:	1899 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Connected load:	24V DC $\pm$ 10%
Power supply:	Included external PSU 100-240V AC
Connection (connector):	M12 A-coded
Connected load PSU:	110-240V AC
Connection PSU:	EURO plug to M12 connector
Degree of protection:	IP40
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-10 °C - +60 °C (14 °F - 140 °F)
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium / plastics
Cover material:	plastic soft
Head width [A]:	298 mm (~11,73")
Length articulated arms:	2x 400 mm (~15,75")
Weight (net):	3250 g (~115 oz)
Gross weight:	3900 g (~138 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Dimmable:	Internal dimmer with memory function
Mounting accessories:	Included table clamp
Made in:	Germany
Feature:	dimmable, short luminaire head

