



LED workplace light with adjustable arm

Product-Nr.	121012-02
EAN:	4260556623726
Model:	CENALED SPOT Articulated Arm

Order number:	121012-02
Model:	CENALED SPOT Articulated Arm
Type:	LED workplace light with adjustable arm
Illuminant:	High Power LED
Power consumption:	~8,5 W
Lamp luminous flux:	1120 lm
Lamp luminous efficiency:	134 lm/W
Light distribution:	Direct
Light colour:	5000K 3-step MacAdam
Colour rendering (Ra):	>80
Connected load:	24V DC $\pm$ 10%
Power supply:	-

Connection (connector):	Connection cable, oil flex, with open cable ends
Degree of protection:	IP67
Class of protection:	III
Beam angle (optics):	30°

Operating temperature:	-10 °C - +50 °C (14 °F - 122 °F)
Lamps lifetime:	> 100,000 h (L90/B10)

Housing material:	aluminium (powder finished)
Cover material:	tempered glass, shatterproof
Length articulated arms:	350 mm (~13,78") / 400 mm (~15,75")

base height:	59 mm (2,32")
Weight (net):	2350 g (~83 oz)
Gross weight:	3000 g (~106 oz)

Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)

Dimmable:	Yes, via push button at the light head, ON/OFF and dimming
------------------	--

Mounting accessories:	Magnet holder plate optional
------------------------------	------------------------------

Made in:	Germany
-----------------	---------

Feature:	universal workplace light with high protection degree
-----------------	---

Abstand d=50 cm

 $E_{\text{spot}} = 3114 \text{ lux}$ $E_{\text{spot}} = 8584 \text{ lux}$ $E_{\text{spot}} = 516 \text{ lux}$ 