



profiled light with t-slot backsided

Product-Nr.	150314-04
EAN:	4260556623894
Model:	PROFILED AC
Order number:	150314-04
Model:	PROFILED AC
Type:	profiled light with t-slot backsided
Illuminant:	SMD LED
Total output incl. driver:	~14 W
Power consumption:	~11 W
Lamp luminous flux:	1670 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	90-305V AC ± 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	connection cable with power plug
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-10 °C -> +45 °C (14 °F -> 113 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 100.000h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (~2,56" x ~1,77")
Length [A]:	500 mm (~19,69")
Weight (net):	1400 g (~49 oz)
Gross weight:	1850 g (~65 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	internal dimmer control
Mounting accessories:	optional
Made in:	Germany
Feature:	universal light , dimmable

