



profiled light with t-slot backsided

| | |
|-----------------------------------|--------------------------------------|
| Product-Nr. | 150614-07 |
| EAN: | 4260556626437 |
| Model: | PROFILED AC |
| Order number: | 150614-07 |
| Model: | PROFILED AC |
| Type: | profiled light with t-slot backsided |
| Illuminant: | SMD LED |
| Total output incl. driver: | ~24 W |
| Power consumption: | ~21 W |
| Lamp luminous flux: | 3340 lm |
| Lamp luminous efficiency: | ~155 lm/W |
| Light distribution: | direct |
| Light colour: | 5600K 3-step MacAdam |
| Connected load: | 90-305V AC ± 10%, 50-60 Hz |
| Power supply: | inbuilt |
| Connection (connector): | Wieland GST18 |
| Degree of protection: | IP40 |
| Class of protection: | I |
| Glare control: | Microprisms |
| Beam angle (optics): | 100° |
| Operating temperature: | -10 °C -> +45 °C (14 °F -> 113 °F) |
| Colour rendering (Ra): | >85 |
| Lamps lifetime: | > 100.000h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | plastics |
| Height [B] x Width [C]: | 65 mm x 45 mm (~2,56" x ~1,77") |
| Length [A]: | 900 mm (~35,43") |
| Weight (net): | 2100 g (~74 oz) |
| Gross weight: | 2650 g (~93 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA |
| Mounting accessories: | optional |
| Made in: | Germany |
| Feature: | universal light |

