



profiled light with t-slot backsided

<b>Product-Nr.</b>	150614-08
<b>EAN:</b>	4260556626444
<b>Model:</b>	PROFILED AC
<b>Order number:</b>	150614-08
<b>Model:</b>	PROFILED AC
<b>Type:</b>	profiled light with t-slot backsided
<b>Illuminant:</b>	SMD LED
<b>Total output incl. driver:</b>	~24 W
<b>Power consumption:</b>	~21 W
<b>Lamp luminous flux:</b>	3340 lm
<b>Lamp luminous efficiency:</b>	~155 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	5600K 3-step MacAdam
<b>Connected load:</b>	90-305V AC ± 10%, 50-60 Hz
<b>Power supply:</b>	inbuilt
<b>Connection (connector):</b>	Wieland GST18
<b>Degree of protection:</b>	IP40
<b>Class of protection:</b>	I
<b>Glare control:</b>	Microprisms
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-10 °C -> +45 °C (14 °F -> 113 °F)
<b>Colour rendering (Ra):</b>	>85
<b>Lamps lifetime:</b>	> 100.000h (L80/B10)
<b>Housing material:</b>	aluminium
<b>Cover material:</b>	plastics
<b>Height [B] x Width [C]:</b>	65 mm x 45 mm (~2,56" x ~1,77")
<b>Length [A]:</b>	900 mm (~35,43")
<b>Weight (net):</b>	2100 g (~74 oz)
<b>Gross weight:</b>	2650 g (~93 oz)
<b>Risk group (DIN EN 62471):</b>	free group
<b>Markings:</b>	CE, UKCA
<b>Dimmable:</b>	internal dimmer control
<b>Mounting accessories:</b>	optional
<b>Made in:</b>	Germany
<b>Feature:</b>	universal light, dimmable

