pofiled light with t-slot backsided

Product-Nr.	150814-08
EAN:	4260556626482
Model:	PROFILED AC





Order number:	150814-08
Model:	PROFILED AC
Type:	pofiled light with t-slot backsided
Illuminant:	SMD LED
Total output incl. driver:	~34 W
Power consumption:	~30 W
Lamp luminous flux:	4676 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Connected load:	120-277V AC ± 10%, 50-60 Hz
Power supply:	Integrated
Connection (connector):	Wieland GST18
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-10 °C - +45 °C (14 °F - 113 °F)
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (~2,56“ x ~1,77“)
Length [A]:	1200 mm (~47,24“)
Weight (net):	2740 g (~97 oz)
Gross weight:	3540 g (~125 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Dimmable:	Internal dimmer control
Mounting accessories:	Optional
Made in:	Germany
Feature:	universal light, dimmable



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com