

LED recessed luminaire for machines



Product-Nr. 153110-11

EAN: 4260556625478

Model: FIELDLED EVO Einbau

Order number: 153110-11

Model: FIELDLED EVO Einbau

Type: LED recessed luminaire for machines

Illuminant: SMD LED

Power consumption: ~39 W

Lamp luminous flux: 6000 lm

Lamp luminous efficiency: 155 lm/W

Light distribution: direct

Light colour: 5600K 3-step MacAdam

Connected load: 24V DC ± 10%

Connection (connector): M12 A-coded, end face

Degree of protection: IP67/IP69K

Class of protection: III

Glare control: Microprisms

Beam angle (optics): 100°

Operating temperature: -30 °C -> +60 °C (-22 °F -> 140 °F)

Colour rendering (Ra): >85

Lamps lifetime: > 100.000h (L80/B10)

Housing material: aluminium

Cover material: ESG (toughened safety glass), shatterproof

Height [B] x Width [C]: 30 mm x 96 mm (~1.18" x ~3.78"), frame: 5.6 mm x 132 mm (~0.22" x ~5.2")

Length [A]: 540 mm (~21,26")

Weight (net): 1900 g (~67 oz)

Gross weight: 2350 g (~83 oz)

Risk group (DIN EN 62471): free group

Markings: CE, UKCA, ETL Listed (5003529)

Dimmable: optional via accessories

Made in: Germany

