

LED surface-mounted light for machines and systems



Product-Nr.	154310-01
EAN:	4260556625867
Model:	TUBELED_25

Order number:	154310-01
Model:	TUBELED_25
Type:	LED surface-mounted light for machines and systems
Illuminant:	SMD LED
Power consumption:	~13 W
Lamp luminous flux:	2015 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	Light Forming Technology
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M8 A-coded
Degree of protection:	IP67
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-30 °C -> +55 °C (-22 °F -> 131 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	safety glass, 4 mm (0,16")
Height [B] x Width [C]:	~23 mm x ~28 mm (~0,91" x ~1,1")
Length [A]:	540 mm (~21,26")
Weight (net):	450 g (~16 oz)
Gross weight:	600 g (~21 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	optional via accessories
Mounting accessories:	optional
Made in:	Germany
Feature:	very slim and bright, M8 sensor connector

