



## LED surface-mounted light



<b>Product-Nr.</b>	154390-11
<b>EAN:</b>	4260556626277
<b>Model:</b>	TUBELED_25 RGB-W IO-Link
Order number:	154390-11
<b>Model:</b>	TUBELED_25 RGB-W IO-Link
<b>Type:</b>	LED surface-mounted light
<b>Illuminant:</b>	SMD LED RGB + W
<b>Power consumption white:</b>	~14,4 W
<b>White lamp luminous flux:</b>	2300 lm
<b>Lamp luminous efficiency:</b>	160 lm/W
<b>Light colour white:</b>	5000K 3-step MacAdam
<b>Power consumption RED:</b>	~4,3 W
<b>Lamp luminous flux RED:</b>	276 lm
<b>Power consumption GREEN:</b>	~2,9 W
<b>Lamp luminous flux GREEN:</b>	504 lm
<b>Power consumption BLUE:</b>	~4,3 W
<b>Lamp luminous flux BLUE:</b>	168 lm
<b>Light distribution:</b>	direct
<b>Connected load:</b>	24 V DC -5 / +10% [LEDs], 24 V DC +/- 25% [IO-Link communication]
<b>Connection (connector):</b>	M8 A-coded
<b>Degree of protection:</b>	IP67
<b>Class of protection:</b>	III
<b>Glare control:</b>	diffused safety glass
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-30 °C -> +55 °C (-22 °F -> 131 °F)
<b>Colour rendering WHITE (Ra):</b>	>85
<b>Lamps lifetime:</b>	> 60.000 h (L80/B10)
<b>Housing material:</b>	aluminum
<b>Cover material:</b>	Safety glass
<b>Height [B] x Width [C]:</b>	~23 mm x ~28 mm (~0,91" x ~1,1")
<b>Length [A]:</b>	540 mm (~21,26")
<b>Weight (net):</b>	450g (~16 oz)
<b>Gross weight:</b>	600g (~21 oz)
<b>Risk group (DIN EN 62471):</b>	free group
<b>Markings:</b>	CE, UKCA
<b>Mounting accessories:</b>	optional
<b>Made in:</b>	Germany
<b>Feature:</b>	Only one light for illumination and signaling, IO-Link