





LED surface-mounted light



| | |
|-------------------------------------|---|
| Product-Nr. | 154490-01 |
| EAN: | 4260556626161 |
| Model: | TUBELED_25 RGB-W |
| Order number: | 154490-01 |
| Model: | TUBELED_25 RGB-W |
| Type: | LED surface-mounted light |
| Illuminant: | SMD RGB-W Cluster LED |
| Power consumption white: | ~19,2 W |
| White lamp luminous flux: | 3072 lm |
| Lamp luminous efficiency: | ~159 lm/W |
| Light colour white: | 5000K 3-step MacAdam |
| Power consumption RED: | ~5,8 W |
| Lamp luminous flux RED: | 368 lm |
| Power consumption GREEN: | ~3,8 W |
| Lamp luminous flux GREEN: | 672 lm |
| Power consumption BLUE: | ~5,8 W |
| Lamp luminous flux BLUE: | 224 lm |
| Light distribution: | direct |
| Connected load: | 24 V DC -10 % +7 % (RGB) – 24 V DC \pm 10 % (W) |
| Connection (connector): | M8 B-coded |
| Degree of protection: | IP67 |
| Class of protection: | III |
| Glare control: | diffused safety glass |
| Beam angle (optics): | 100° |
| Operating temperature: | -30 °C -> +55 °C (-22 °F -> 131 °F) |
| Colour rendering WHITE (Ra): | >85 |
| Lamps lifetime: | > 60.000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | safety glass, shatterproof |
| Height [B] x Width [C]: | ~23 mm x ~28 mm (~0,91" x ~1,1") |
| Length [A]: | 705 mm (~27,76") |
| Weight (net): | 570 g (~20 oz) |
| Gross weight: | 700 g (~25 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | option external, PWM |
| Mounting accessories: | option |
| Made in: | Germany |
| Feature: | RGB-W: Illumination and beacon in one light; connection |