

Datenblatt Art. 902.0815

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

DESK Steckdosenleiste / DESK power strip

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung Frequenz	16A / 250V~ 50Hz	Rated current / rated voltage Frequency	16A / 250V~ 50Hz
Netzanschluss		Power supply	
Zuleitung		Supply cable	
Stecker	Installationssteckverbinder	Plug	Building installation connector
Ableitung Kupplung Installationssteckverbinder		Through cable Coupling Building installation connector	
2-polig mit Schutzkontakt Schwarz, ähnlich RAL 9005 20A / 250V~, IP20		2-pole with earthing contact Black, similar to RAL 9005 20A / 250V~, IP20	
Stromausgang		Power output	
Steckdosen		Socket outlets	
2x CEE 7/3 (Type F)		2x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz Schwarz, ähnlich RAL 9005, 35° 16A / 250V~, IP20		2-pole with earthing contact With shutter Black, similar to RAL 9005, 35° 16A / 250V~, IP20	
Funktionsmodule		Function modules	
Custom Module 1x Custom Modul leer		Custom Modules 1x Custom Module empty	
USB-C Charger 30 W (42,5 mm)		USB-C Charger 30 W (42,5 mm)	
Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C port	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 2.5 A 22.5 W DC 15.0 V 2.0 A 30.0 W	Output voltage / Output current / Output power C port	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 2.5 A 22.5 W DC 15.0 V 2.0 A 30.0 W
Ausgangsspannung / Ausgangsstrom / Ausgangsleistung QC port	DC 9.0 V 2.0 A 18.0 W DC 12.0 V 1.5 A 18.0 W	Output voltage / Output current / Output power QC port	DC 9.0 V 2.0 A 18.0 W DC 12.0 V 1.5 A 18.0 W
Durchschnittseffizienz		Average active efficiency	
C port DC 5.0 V 3.0 A 15.0 W	83.3 %	C port DC 5.0 V 3.0 A 15.0 W	83.3 %
C port DC 9.0 V 2.5 A 22.5 W	86.3 %	C port DC 9.0 V 2.5 A 22.5 W	86.3 %
C port DC 15.0 V 2.0 A 30.0 W	88.1 %	C port DC 15.0 V 2.0 A 30.0 W	88.1 %
C port DC 20 V 1.4 A 28.0 W	87.0 %	C port DC 20 V 1.4 A 28.0 W	87.0 %
C port QC DC 9.0 V 2.0 A 18.0 W	85.9 %	C port QC DC 9.0 V 2.0 A 18.0 W	85.9 %
C port QC DC 12.0 V 1.5 A 18.0 W	86.4 %	C port QC DC 12.0 V 1.5 A 18.0 W	86.4 %

Effizienz bei niedriger Last (10 %)		Efficiency at low load (10 %)	
C port DC 5.0 V 3.0 A 15.0 W	79.0 %	C port DC 5.0 V 3.0 A 15.0 W	79.0 %
C port DC 9.0 V 2.5 A 22.5 W	79.7 %	C port DC 9.0 V 2.5 A 22.5 W	79.7 %
C port DC 15.0 V 2.0 A 30.0 W	80.6 %	C port DC 15.0 V 2.0 A 30.0 W	80.6 %
C port DC 20 V 1.4 A 28.0 W	76.6 %	C port DC 20 V 1.4 A 28.0 W	76.6 %
C port QC DC 9.0 V 2.0 A 18.0 W	82.8 %	C port QC DC 9.0 V 2.0 A 18.0 W	82.8 %
C port QC DC 12.0 V 1.5 A 18.0 W	79.0 %	C port QC DC 12.0 V 1.5 A 18.0 W	79.0 %
Leistungsaufnahme bei Nulllast		No-load power consumption	
	0.08 W		0.08 W
Ladestandard		Charging standards	
Power Delivery	USB 3.1 PD	Power Delivery	USB 3.1 PD

Weitere Produkteigenschaften

Further product attributes

Plattform	Standard (kHE)	Plattform	Standard (kHE)
------------------	----------------	------------------	----------------

Material

Gehäuse:
Aluminium, eloxiert

Abdeckung:
PA6 GF30 850°C, schwarz ähnlich RAL 9005

Lieferumfang

1x DESK Steckdosenleiste
inkl. Haltewinkel

Im Karton

Material

Housing:
Aluminium, anodised

Cover:
PA6 GF30 850°C, black similar to RAL 9005

Scope of delivery

1x DESK power strip
incl. Mounting brackets

In carton

Umgebungsbedingungen

Maximale Höhe	0 - 2000m
Umgebungstemperatur bei Montage und Nutzung	5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.	
Umgebungstemperatur bei Transport und Lagerung	-20 °C - 60 °C
Relative Luftfeuchtigkeit (nicht kondensierend)	10 % - 90 %
Luftdruck	80-108 kPa
Schutzart	IP20

Environmental conditions

Maximum height	0 - 2000m
Surrounding temperature during mounting and use	5°C – 35°C
Protect from direct sunlight.	
Surrounding temperature during transport and storage	-20 °C - 60 °C
Relative humidity (non-condensing)	10 % - 90 %
Air pressure	80-108 kPa
Protection type	IP20

Konformität

Angewandte Normen	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)
--------------------------	---

Conformity

Applied standards	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)
--------------------------	---