

Datenblatt Art. 937.304

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

DESK2 ALU BLACK Steckdosenleiste / DESK2 ALU BLACK power strip

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50Hz	Frequency	50Hz
Netzanschluss		Power supply	
Zuleitung	0,2m H05VV-F 3G1,5mm ²	Supply cable	0,2m H05VV-F 3G1,5mm ²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	Installationsstecker	Plug	Building installation plug
Stromausgang		Power output	
Steckdosen		Socket outlets	
2x CEE 7/3 (Type F)		2x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Mit erhöhtem Berührungsschutz		With shutter	
Schwarz, ähnlich RAL 9005, 35°		Black, similar to RAL 9005, 35°	
16A / 250V~, IP20		16A / 250V~, IP20	
Funktionsmodule		Function modules	
Custom Module		Custom Modules	
1x Custom Module leer		1x Custom Modules empty	
USB A&C Charger 22W (42,5mm)		USB A&C Charger 22W (42,5mm)	
Output C	DC5V 3.0A DC9V 2.3A DC15V 1.4A DC20V 1.1A	Output C	DC5V 3.0A DC9V 2.3A DC15V 1.4A DC20V 1.1A
Output Q	DC5V 3.0A DC9V 2.0A DC12V 1.5A	Output Q	DC5V 3.0A DC9V 2.0A DC12V 1.5A
C port + Q port (beide Ausgänge)	C port: DC5V 2.0A; Q port: DC5V 1.5A	C port + Q port (both output)	C port: DC5V 2.0A; Q port: DC5V 1.5A

Weitere Produkteigenschaften		Further product attributes	
Tischplattenstärke Plattform	10-40mm Standard (kHE)	Tabletop thickness Platform	10-40mm Standard (kHE)
Material Gehäuse: Aluminium, eloxiert Endkappen: ABS 680°C, schwarz ähnlich RAL 9005 Abdeckung: PA6 GF30 850°C, schwarz ähnlich RAL 9005		Material Housing: Aluminium, anodised End caps: ABS 680°C, black similar to RAL 9005 Cover: PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang 1x DESK2 Steckdosenleiste inkl. Haltewinkeln Im Karton		Scope of delivery 1x DESK2 power strip incl. Mounting brackets In carton	
Umgebungsbedingungen		Environmental conditions	
Maximale Höhe	0 - 3000m	Maximum height	0 - 3000m
Umgebungstemperatur bei Montage und Nutzung	5°C – 35°C	Surrounding temperature during mounting and use	5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.		Protect from direct sunlight.	
Umgebungstemperatur bei Transport und Lagerung	-25°C - 60°C	Surrounding temperature during transport and storage	-25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend)	5 – 95%	Relative humidity (non-condensing)	5 – 95%
Schutzart	IP20	Protection type	IP20
Konformität / Approbation		Conformity / Approval	
Bauart geprüft	DIN VDE 0620-1 / Bauart DIN 49440 / CEE 7/3	Type approved	DIN VDE 0620-1 / construction type DIN 49440 / CEE 7/3