

Datenblatt Art. 936.003

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

VENID

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Netzanschluss		Power supply	
Zuleitung	0,2m H05VV-F 3G1,5mm²	Supply cable	0,2m H05VV-F 3G1,5mm²
Nicht wiederanschließbar Mit Schraubklemme		non rewirable With screw terminals	
Stecker	Installationsstecker	Plug	Building installation plug
Stromausgang		Power output	
Steckdosen		Socket outlets	
1x CEE 7/3 (Type F)		1x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz Schwarz, ähnlich RAL 9005, 35° 16A 250V~, IP20		2-pole with earthing contact With shutter Black, similar to RAL 9005, 35° 16A 250V~, IP20	
Funktionsmodule		Function modules	
Custom Module		Custom Modules	
2x Custom Module leer		2x Custom Modules empty	
1x USB-Charger		1x USB charger	
Doppelcharger	3,1A / 5VDC	Double charger	3,1A / 5VDC
Weitere Produkteigenschaften		Further product attributes	
Material		Material	
Gehäuse: Aluminium, eloxiert		Housing: Aluminium, anodised	
Abdeckung: PA6 GF30 850°, schwarz ähnlich RAL 9005		Cover: PA6 GF30 850°C, black similar to RAL 9005	
Träger stromführende Teile (Steckdosentopf): PA6 GF30 850°C, schwarz ähnlich RAL 9005		Carrier live parts (sockets): PA6 GF30 850°C, black similar to RAL 9005	
Montage		Mounting	
In VENID Einbaurahmen		In VENID built-in frame	

Lieferumfang

1x VENID Steckdosenleiste Medium
4x Haltewinkel
Mit Schrauben
Im Karton

Zubehör

VENID Einbaurahmen
VENID Wanne

Scope of delivery

1x VENID power strip medium
4x mounting brackets
With screws
In carton

Accessories

VENID built-in frame
VENID tank

Umgebungsbedingungen

Environmental conditions

Maximale Höhe	2000 m	Maximum height	2000 m
Umgebungstemperatur bei Montage und Nutzung	-5°C – 35°C	Surrounding temperature during mounting and use	-5°C – 35°C
Umgebungstemperatur bei Transport und Lagerung	-25° - 60°	Surrounding temperature during transport and storage	-25° - 60°
Schutzart	IP20	Protection type	IP20