

Datenblatt Art. 919.2001

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

Consolidation Point Unit Small

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	20A / 250V~	Rated current / rated voltage	20A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	Installationsstecker	Supply cable	Building installation plug
Stecker		Plug	
in Profilrückseite		in profile backside	
Stromausgang		Power output	
Steckdosen		Socket outlets	
3x Installationskupplung		3x Building installation coupling	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Schwarz, ähnlich RAL 9005, 90°		Schwarz, ähnlich RAL 9005, 90°	
20A 250V~, IP20		20A 250V~, IP20	
2-phasig		2-phase	
3x Installationskupplung		3x Building installation coupling	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Lachsrot, 90°		Salmon pink, 90°	
20A 250V~, IP20		20A 250V~, IP20	
2-phasig		2-phase	
Weitere Produkteigenschaften		Further product attributes	
Plattform	Standard (kHE)	Platform	Standard (kHE)
Material		Material	
Gehäuse:		Housing:	
Aluminium, eloxiert		Aluminium, anodised	
Abdeckung:		Cover:	
PA6 GF30 850°C, schwarz ähnlich RAL 9005		PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang		Scope of delivery	
1x Consolidation Point Unit Small		1x Consolidation Point Unit power	
inkl. selbstklebende Beschriftungstreifen 15x35mm		incl. adhesive labeling strips 15x35mm	
Zubehör		Accessories	
Consolidation Point Halterung Small		Consolidation Point bracket small	
Im Polybeutel		Packed in polybag	