

Datenblatt Art. 919.2004

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

Consolidation Point Unit Strom Large

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung		Supply cable	
Stecker	Installationsstecker	Plug	Building installation plug
Farbe	schwarz	Colour	black
Stecker	Installationsstecker	Plug	Building installation plug
Farbe	lachsrot	Colour	salmon pink
Stecker	Installationsstecker	Plug	Building installation plug
Farbe	kieselgrau	Colour	pebble grey
in Profilrückseite		in profile backside	
Stromausgang		Power output	
Steckdosen		Socket outlets	
4x Installationskupplung		4x Building installation coupling	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Schwarz, ähnlich RAL 9005, 90°		Schwarz, ähnlich RAL 9005, 90°	
20A 250V~, IP20		20A 250V~, IP20	
3-phasig		3-phase	
4x Installationskupplung		4x Building installation coupling	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Lachsrot 90°		Salmon pink 90°	
20A 250V~, IP20		20A 250V~, IP20	
3-phasig		3-phase	
4x Installationskupplung		4x Building installation coupling	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Kieselgrau 90°		Pebble grey 90°	
20A 250V~, IP20		20A 250V~, IP20	
3-phasig		3-phase	
Weitere Produkteigenschaften		Further product attributes	
Plattform	Standard (kHE)	Plattform	Standard (kHE)

Material

Gehäuse:
Aluminium, eloxiert

Abdeckung:
PA6 GF30 850°C, schwarz ähnlich RAL
9005

Lieferumfang

1x Consolidation Point Unit Strom Large
inkl. selbstklebende Beschriftungsstreifen
15x35mm

Im Polybeutel

Material

Housing:
Aluminium, anodised

Cover:
PA6 GF30 850°C, black similar to RAL 9005

Scope of delivery

1x Consolidation Point Unit power Large
incl. adhesive labeling strips 15x35mm

Packed in polybag