

plug - with TE screw terminals, for harsh applications





Product description	
BALS-Prd.-Nr	2189-1
EAN	4024941399654
Product category	TE plug
Current	63A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~
Frequency	50/60Hz

Product description	
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Collar red RAL 3000, Pusher black RAL 9005, Housing cover dark grey RAL 7012, Cable gland dark grey RAL 7012, Bajonet ring dark grey RAL 7012
Connection design	screw terminal as box terminal
Maximum conductor size	16,0 qmm
Cable entry	with cable gland
Height	234mm
Width	114mm
Depth	114mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter from 16 up to max. 36 mm, Screwless housing connection, With rubberized cable gland (SUSTAINABLE-GRIP), With rubberized bayonet ring (SUSTAINABLE-GRIP), Multi-Grip cable gland with gasket and integrated strain relief

Logistics data	
Weight/pcs	761.06 g / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
Length	114 mm
Width	114 mm
Height	234 mm
Weight	762.06 g
Packaging	Carton
Content amount	5 ST
Length	325 mm
Width	217 mm
Height	210 mm
Weight	4,011.3 g
Volume	14,810.25 ccm



Ampere Polzahl	63 3	63 4	63 5
ø a	114,0	114,0	114,0
b	153,0	153,0	153,0
d	171,0	171,0	171,0
ø e	36,0	36,0	36,0
x	233,0	233,0	233,0
y	114,0	114,0	114,0
z	114,0	114,0	114,0
Cond. mm ² min	6,0	6,0	6,0
Cond. mm ² max	16,0	16,0	16,0



