

LED surface mounted luminaire, decorative
Article no. 10002250



Tender	
Decorative surface-mounted LED ceiling light, , height 125 mm, weight 0.495 kg, with rotationally symmetrical narrow-wide beam light distribution. Rated output 5 W, light color warm white, most similar color temperature (CCT) 3,100 K, general color rendering index, housing material: aluminum, color: aluminum, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): I, degree of protection (DIN EN 60529): IP20. With electronic control gear, dimmable.	

Article data	
Article no.	10002250
GTIN	4250047765172
Short description	LED surface mounted luminaire, decorative
Material	Aluminium
Colour	Alu
Type of surface	Matt
Outer diameter	94 mm
Hight	125 mm
Scope of delivery	Incl. converter for connection to the 230-V mains voltage
Weight	0.495 kg
Conformance	CE, UKCA

LED surface mounted luminaire, decorative

Article no. 10002250

Lighting technology	
Colour temperature	3.100 K
Light output	Direct
System efficiency	5 lm/W
Beam angle	20°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Swivel angle	55°
Rotation angle	355°

Packing data	
Gross weight	0.55 kg
Length of packaging	100 mm
Packaging width	100 mm
Packaging height	120 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.