


QUALITYFLEX Individual Segment of LED flex lighting TunableWhite
HE, 50 mm, CRI > 90, 20 W / m, IP00
 Article no. 75566004



Tender

Segment of LED Flexplatine TunableWhite HE, 50 mm, CRI>90, 20 W / m, IP00, LED white light, 6,500K-2,700K, CRI > 90 LED Flexplatine for decorative, technical and efficient illumination of cove lighting, linear applications and backlighting, ambient and general lighting of rooms, architectural applications and for areas where high illumination is required, such as indirect or direct lighting, luminous ceilings, restaurant lighting and much more. Length: 50.0 mm Lamp wattage per meter: 20.0 W/m, degree of protection on room side: IP00, protection class: III, voltage: 24V DC, beam angle: 120.0 °, 160 LEDs per meter, chip spacing (short pitch): 6.25 mm. The LED flex board can be shortened every 50 mm for individual applications. The maximum system length of 5,000mm must not be exceeded with one feed.

Product Benefits

- Highly efficient TunableWhite LED flex board.
- Color temperature and brightness can be changed with 2-channel dimming.
- Optimally controllable via DALI (DT8) or TunableWhite radio remote control.
- Protection class: IP00
- Color temperature: 2,700 Kelvin to 6,500 Kelvin.
- Short pitch: 6.25 mm.
- High color rendering with CRI>90.

QUALITYFLEX Individual Segment of LED flex lighting TunableWhite HE, 50 mm, CRI > 90, 20 W / m, IP00
 Article no. 75566004

Article data	
Article no.	75566004
GTIN	4255752515630
Series name	QUALITYFLEX Individual
Short description	Segment of LED flex lighting TunableWhite HE, 50 mm, CRI > 90, 20 W / m, IP00
Colour	White
Length	50 mm
Width	10 mm
Height	2 mm
Scope of delivery	incl. 1 x assembly instructions
Weight	0.090 kg
Length of the connection line	350 mm
Conformance	CE

Lighting technology	
Colour temperature	2.700 K - 6.500 K
Light colour	White
Color Temperature 1	2,700 K
Color Temperature 2	6,500 K
Luminous flux 1	1,290 lm/m
Luminous flux 2	1,475 lm/m
System efficiency	20 lm/W
McAdam-Step	McAdam-Step 5
Colour rendering	CRI > 90
Beam angle	120°
Adjustable color temperature	Infinite control

Operating technology of the luminaire	
System output	100 W
Lamp power per meter	20 W/m
Voltage type	DC
DC nominal voltage max	24 V
Lamp	LED
Protection class	III
Degree of protection	IP00
Ambient temperature	-10 °C to +40 °C
Dimmable	Yes
Wire number	3
Control	Depending on driver
Length of the connection line	350 mm
Cable assignment	red = + pole white = - pole, cold white yellow = - pole, warm white
Design of the connecting cable	one-sided
Bulb change possible	No
Rated life time L70/B50 at 25 °C	181,000 h
Rated life time L80/B10 at 25 °C	123000 h
Energy efficiency class	nicht erforderlich

QUALITYFLEX Individual Segment of LED flex lighting TunableWhite
HE, 50 mm, CRI > 90, 20 W / m, IP00
 Article no. 75566004

Operating technology of QualityFlex	
Power per meter	20 W/m
Short Pitch	6.25 mm
Number of lamps per meter	160 Qty
Length of individual sections	50 mm
Smallest bend radius	30 mm
Control	Negative (3-core)
Length	50 mm
Maximum module length	5,000 mm
Circuit type	Parallel conduction
LED Type	2835 LED

Packing data	
Gross weight	0.14 kg
Length of packaging	N.N.
Packaging width	N.N.
Packaging height	N.N.
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Compatible Driver						
Article no.	Power min	Power	Control	Length	Width	Hight
17206000	1 W	20 W	1-10 V	146 mm	55 mm	19 mm
17207000	1 W	30 W	on/off	160 mm	50 mm	22 mm
17214000	1 W	7.2 W	on/off	68 mm	35 mm	21 mm
17223000	1 W	75 W	on/off	185 mm	60 mm	31 mm
17224000	1 W	100 W	on/off	199 mm	63 mm	36 mm
17225000	1 W	150 W	on/off	219 mm	63 mm	36 mm
17226000	1 W	240 W	on/off	244 mm	71 mm	38 mm
17227000	1 W	320 W	on/off	252 mm	90 mm	44 mm
17228000	1 W	480 W	on/off	262 mm	125 mm	44 mm
17240000	1 W	20 W	on/off	150 mm	40 mm	30 mm
17241000	1 W	40 W	on/off	210 mm	40 mm	30 mm
17242000	1 W	60 W	on/off	250 mm	40 mm	30 mm
17243000	1 W	120 W	on/off	300 mm	40 mm	30 mm
17244000	1 W	150 W	on/off	310 mm	40 mm	30 mm
17260000	1 W	150 W	on/off	105 mm	90 mm	59 mm

QUALITYFLEX Individual Segment of LED flex lighting TunableWhite
HE, 50 mm, CRI > 90, 20 W / m, IP00

Article no. 75566004

Compatible Controller						
Article no.	Power min	Power	Control	Length	Width	Hight
18151000	1 W	240 W	KNX	170 mm	59 mm	30 mm
18152000	1 W	240 W	DALI-DT6	170 mm	59 mm	30 mm
18153000	1 W	240 W	DMX	170 mm	59 mm	30 mm
18154000	1 W	240 W	1-10 V	170 mm	59 mm	30 mm
18155000	1 W	240 W	DALI-2	170 mm	59 mm	30 mm
18156000			1-10 V	167 mm	51 mm	23 mm
18157000	1 W	240 W	ZigBee	145 mm	46.5 mm	16 mm
18161000	1 W	240 W	KNX	72 mm	90 mm	70 mm
18162000	1 W	240 W	DALI-DT6	54 mm	110 mm	66 mm
18164000	1 W	240 W	1-10 V	54 mm	110 mm	66 mm
18165000	1 W	240 W	DALI-2	54 mm	110 mm	66 mm
17518000	1 W	240 W	Wireless technology control			
18192000	1 W	240 W	Wireless technology control	160 mm	45 mm	18 mm
17290000	1 W	100 W	DALI-2	244 mm	64 mm	32 mm
17291000	1 W	200 W	DALI-2	330 mm	79 mm	39 mm

QUALITYFLEX Individual Segment of LED flex lighting TunableWhite
HE, 50 mm, CRI > 90, 20 W / m, IP00
 Article no. 75566004

Compatible Profiles				
Short description	Series name	Length	Width	Hight
Recessed profile 53654070	P36-20	2,000 mm	30 mm	20.4 mm
LED recessed profile 53759070	P40-30	2,000 mm	44.4 mm	24 mm
Wall recessed profile 53650260	P32-12	2,000 mm	19.1 mm	81 mm
Plaster profile 53655070	P37-30	2,000 mm	63.4 mm	15.9 mm
Plaster profile 53656070	P38-30	2,000 mm	63.4 mm	24 mm
Surface-mounted profile 53600070	P01-10	2,000 mm	20 mm	8 mm
Surface-mounted profile 53602070	P04-14	2,000 mm	24 mm	9 mm
Surface-mounted profile 53603070	P06-20	2,000 mm	23 mm	25.1 mm
LED surface-mounted profile 53606070	P30-30	2,000 mm	33.4 mm	29.6 mm
Surface-mounted profile 53607080	P16-16	2,000 mm	18.8 mm	18.6 mm
Surface-mounted profile, flat 53380261	ONE		17.6 mm	6 mm
Surface-mounted profile, high 53381302	ONE		17.6 mm	15.9 mm
Surface-mounted corner profile 53700070	P60-10	2,000 mm	20 mm	16 mm
Surface-mounted corner profile 53702070	P62-14	2,000 mm	24 mm	19.4 mm
Surface-mounted corner profile 53385261	ONE		24 mm	19.4 mm
Flexible profile 53753260	P72-12	2,000 mm	20 mm	3.3 mm
Wall surface-mounted profile 53754070	P73-12	2,000 mm	17.8 mm	46.1 mm
Wall surface-mounted profile 53751260	P74-14	2,000 mm	18.5 mm	55 mm
Surface-mounted round profile 53760260	P90-16	2,000 mm	20 mm	17.04 mm