




BARENT LED-Einbaudownlight

Article no. 12104173



Tender

LED-Einbaudownlight, Round. Toolless ceiling installation by leaf spring. Ceiling cut-out Ø 56 mm, Installation depth 11 mm, Outer diameter 69 mm, Weight 0,085 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, transparent. Luminous flux 380 lm, Power 1 x 4 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 90, Housing material: Aluminium / Plastic, Colour: White structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. Depending on driver dimmable.

Product Benefits

- Verwendbar für den Standardausschnitt von 56 mm.
- Geringe Einbautiefe von 11 mm.
- Deckenstärke mindestens 4 mm.
- Hohe Farbwiedergabe (CRI>90).
- Ausgestattet mit Anschlußleitung von 3.000 mm.
- Damit kann das Betriebsgerät (Betriebsstrom: 350 mA) sehr einfach an geeigneter Stelle untergebracht werden.
- Massive Ausführung aus Aluminiummaterial.
- Bei geeignetem Betriebsgerät: dimmbar.


BARENT LED-Einbaudownlight

Article no. 12104173

Article data	
Article no.	12104173
GTIN	4255752519744
Series name	BARENT
Short description	LED-Einbaudownlight
Material	Aluminium / Plastic
Colour	White
Type of surface	Structure
Shape	Round
Outer diameter	69 mm
Built-in diameter min.	56 mm
Built-in diameter	56 mm
Installation depth	11 mm
Hight	6 mm
Scope of delivery	inkl. Anschlußleitung 3.000 mm
Weight	0.085 kg
Conformance	CE, UKCA

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	380 lm
System efficiency	95 lm/W
Colour rendering	CRI > 90
Reflector	Faceted
Reflector colour	silver
Beam angle	60°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	4 W
Voltage type	DC
Current	350 mA
Lamp	LED
Lamp holder	Without fitting
Protection class	III
Degree of protection	IP20
Dimmable	Depending on type of control gear
Control	Depending on driver
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Further references	No cover with thermal insulation material
Material cover	Plastic, transparent
Suitable for through-wiring	Yes, with optional accessories


BARENT LED-Einbaudownlight

Article no. 12104173

Packing data	
Gross weight	0.131 kg
Length of packaging	95 mm
Packaging width	90 mm
Packaging height	75 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Required accessories	
Article no.: 17662010	
LED converter 350 mA, on/off switchable	
Power: 1 - 7,2 W, ohne Konfektionierung	
Dimensions: 68 mm x 35 mm x 21 mm	
https://www.brumberg.com/fileadmin/products/Datenblatt_17662010_2021_DE.pdf	
Article no.: 17613010	
LED-Konverter 350 mA, schaltbar	
Power: 1 - 15 W, ohne Konfektionierung	
Dimensions: 115 mm x 34 mm x 19 mm	
https://www.brumberg.com/fileadmin/products/Datenblatt_17613010_2021_DE.pdf	
Article no.: 17621010	
LED converter 350 mA, on/off switchable	
Power: 1 - 21 W, ohne Konfektionierung	
Dimensions: 128 mm x 50 mm x 13 mm	
https://www.brumberg.com/fileadmin/products/Datenblatt_17621010_2021_DE.pdf	
Article no.: 17663010	
LED converter 350 mA, trailing-edge phase dimmable	
Power: 2,8 - 7 W, ohne Konfektionierung	
Dimensions: 110 mm x 50 mm x 19 mm	
https://www.brumberg.com/fileadmin/products/Datenblatt_17663010_2021_DE.pdf	
Article no.: 17648010	
LED converter 350 mA, trailing-edge phase dimmable	
Power: 0,7 - 17 W, ohne Konfektionierung	
Dimensions: 166 mm x 46 mm x 34 mm	
https://www.brumberg.com/fileadmin/products/Datenblatt_17648010_2021_DE.pdf	
Article no.: 17684010	
LED converter 350 mA, DALI dimmable (digital)	
Power: 2,8 - 7 W, ohne Konfektionierung	
Dimensions: 130 mm x 42 mm x 22 mm	
https://www.brumberg.com/fileadmin/products/Datenblatt_17684010_2021_DE.pdf	
Article no.: 17658010	
LED round converter 350 mA, DALI dimmable (digital)	
Power: 2,1 - 9 W, ohne Konfektionierung	
Dimensions: 56 mm x 25 mm	
https://www.brumberg.com/fileadmin/products/Datenblatt_17658010_2021_DE.pdf	



BRUMBERG

Light. Since 1873.

BARENT LED-Einbaudownlight

Article no. 12104173

Optional accessories

Article no.: 83330000

Connection box 230 V AC, 3-pole

Dimensions: 80 mm x 41 mm x 34 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_83330000_2021_DE.pdf

Article no.: 83331000

Connection box 230 V AC, 5-pole (DALI / 1-10 V)

Dimensions: 95 mm x 55 mm x 30 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_83331000_2021_DE.pdf