


GEORGA LED surface-mounted light, 2CCT, switchable

Article no. 57428183













Tende

LED surface-mounted light, 2CCT, switchable, Round.Luminaire diameter 600.0 mm, Hight 110.0 mm Weight 3.79 kg, with rotattionssymmetrical, deep, wide distributed light intensity. Cover plastic, opal. Luminous flux 2.730 lm, Power 1 x 38 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Rated life time L70/B50 at 25 °C: 50.000 h, Rated life time L80/B50 at 25 °C: 50.000 h, Housing material: Steel / Plastic, Colour: White structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20. With electronic driver, on/off switchable.

| Article data | |
|-------------------|---|
| Article no. | 57428183 |
| GTIN | 4255752522799 |
| Series name | GEORGA |
| Short description | LED surface-mounted light, 2CCT, switchable |
| Material | Steel / Plastic |
| Colour | White |
| Type of surface | Structure |
| Shape | Round |
| Outer diameter | 600 mm |
| Hight | 110 mm |
| Scope of delivery | incl. converter for connection to 230 V mains voltage |
| Weight | 4.800 kg |
| Conformance | CE, UKCA |



GEORGA LED surface-mounted light, 2CCT, switchable

Article no. 57428183

| Lighting technology | |
|------------------------------|-------------------|
| Colour temperature | 3.000 K / 4.000 K |
| Light colour | White |
| Light output | Direct |
| Luminous flux | 2,730 lm |
| System efficiency | 72 lm/W |
| McAdam-Step | McAdam-Step 3 |
| Colour rendering | CRI > 80 |
| Reflector | Without |
| Beam angle | 110° |
| Light sharing | Symmetric |
| Adjustable color temperature | Stages |

| Operating technology of the luminaire | |
|---------------------------------------|--|
| System output | 38 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequency max | 50 Hz |
| Lamp | LED |
| Protection class | |
| Degree of protection | IP20 |
| Control | on/off |
| Bully shange passible | The light source of this luminaire may only be replaced by the manufacturer or a service |
| Bulb change possible | technician commissioned by him or a similarly qualified person. |
| Rated life time L70/B50 at 25 °C | 50,000 h |
| Rated life time L80/B50 at 25 °C | 50.000 h |

| Mounting technology | |
|-----------------------|------------------|
| Mounting method | Surface mounting |
| Place of installation | Ceiling-mounted |
| Adjustability | Not adjustable |
| Material cover | Plastic, opal |

| Packing data | |
|-------------------------|---|
| Gross weight | 5.95 kg |
| Length of packaging | 640 mm |
| Packaging width | 640 mm |
| Packaging hight | 150 mm |
| | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. |
| Disposal at end of life | By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that |
| | harmful substances get into the environment. |