




**PEPA RONDO LED track spotlight 48 V DC, DALI-2 dimmable**  
Article no. 43130083



**Tender**  
Round LED track spotlight 48 V DC, DALI-2 dimmable, luminaire diameter 45 mm, height 100 mm, weight 0.216 kg, white reflector with rotationally symmetrical narrow-wide beam light distribution. Transparent plastic cover, rated luminous flux 680 lm, rated wattage 1 x 8 W, warm white light color, most similar color temperature (CCT) 3,000 K, general color rendering index CRI > 90, service life L70/B50 at 25 °C: 50,000 h, housing material: aluminum / polycarbonate, color: black, permissible ambient temperature (ta): 0°C to +35°C, protection class (EN 61140): III, degree of protection (DIN EN 60529): IP20. For connection to an external control gear, which is not included with the luminaire. DALI-2 dimmable.

Article data	
Article no.	43130083
GTIN	4255752520429
Series name	PEPA RONDO
Short description	LED track spotlight 48 V DC, DALI-2 dimmable
Material	Aluminium / Polycarbonate
Colour	Black
Type of surface	Matt
Shape	Round
Outer diameter	45 mm
Hight	100 mm
Scope of delivery	inkl. DALI-2 Adapter
Weight	0.216 kg
Conformance	CE, UKCA

**PEPA RONDO LED track spotlight 48 V DC, DALI-2 dimmable**

Article no. 43130083

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	680 lm
System efficiency	85 lm/W
McAdam-Step	McAdam-Step 6
Colour rendering	CRI > 90
Reflector	Other
Reflector colour	white
Beam angle	25°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	8 W
Voltage type	DC
AC nominal voltage min	48 V
AC nominal voltage max	48 V
Current	200 mA
Lamp	LED
Lamp holder	LED
Protection class	III
Degree of protection	IP20
Ambient temperature	0°C bis +35°C
Dimmable	Yes
Control	DALI-2
Minimum / maximum dimming range	1 - 100 %
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	50,000 h
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Conductor rail mounting
Place of installation	Ceiling- /Wall-mounted
Adjustability	Rotable and pivoted
Swivel angle	90°
Rotation angle	355°
Material cover	Plastic, transparent
Suitable for through-wiring	No

Packing data	
Gross weight	0.272 kg
Length of packaging	185 mm
Packaging width	125 mm
Packaging height	50 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>