



# INSTRUCTION



# REGIOLUX


Regiolux GmbH  
 Hellinger Str. 3  
 D-97486 Königsberg/Bay.  
 T 09525 89-0  
 www.regiolux.de  
 info@regiolux.de

## CAMU 3781



CAMU ETM + DPSN/DPSNA ✓  
 CAMU flex10D + DPSN/DPSNA ✓  
 CAMU DALI + DPSN/DPSNA ✓

CAMU ETM + DPS ✓  
 CAMU flex10D + DPS ✓  
 CAMU DALI + DPS ✗



Diese Leuchte enthält ein Leuchtmittel der Energieeffizienzklasse **B** (LF940), **C** (LF930)

This luminaire contains a light source of energy efficiency class **B** (LF940), **C** (LF930)

✓ ETM  
 ✗ DALI / flex10D

930 / 940		
300 mA	~ 1800/1900 lm	12 W
350 mA	~ 2100/2200 lm	14 W
400 mA	~ 2300/2400 lm	16 W
450 mA	~ 2600/2700 lm	19 W
<b>500 mA</b>	<b>~ 2900/3000 lm</b>	<b>21 W</b>
550 mA	~ 3100/3300 lm	23 W
600 mA	~ 3400/3600 lm	25 W
650 mA	~ 3600/3900 lm	28 W
700 mA	~ 3900/4100 lm	30 W
750 mA	~ 4200/4400 lm	32 W
800 mA		
850 mA		
900 mA	not released / nicht freigegeben	
950 mA		
1000 mA		
1050 mA		

\* Werkseinstellung - Factory setting

I-out	Im	Psys
~	~	~
~	~	~
~	~	~

### flex10D

# MONTAGE

1

DPSN/DPSNA  
 DPS DALI ✗  
 ETM / flex10D ✓

CAMU

2

3

4

0 = OFF  
 1 = L1  
 2 = L2  
 3 = L3

Alternativ

20°	CAMU/95 R 20° 3780 1010 120
30°	CAMU/95 R 30° 3780 1010 130
*40°	CAMU/95 R 40° 3780 1010 140
60°	CAMU/95 R 60° 3780 1010 160

\*Standard

Option +

CAMU/95 GS  
 3780 1020 100

Replace

CAMU/95 RR  
 3780 1030 100