




CEE-Box 16-2, 2x CEE 16 A IP54/4x Schuko 16 A IP54



4 046725 402275

Leistungsmerkmale

Die RED CEE-BOX 16-2 Steckdosenkombination zur festen Wandmontage ist komplett montiert und anschlussfertig verdrahtet. Die RED CEE-BOX wurde zur Verwendung in Umgebungen bis zu einer Schutzart von IP54 konzipiert.

Dank der professionellen Verdrahtung mit hochwertigen Schutzschaltgeräten können wir eine erhöhte Sicherheit gem. DIN EN 61439 gewährleisten. Die Schutzschaltgeräte sind unter einer transparenten und schlagfesten Betätigungsclappe eingebaut. Die Steckdosen sind aus schlagfestem Polyamid. Alle Steckdosenkombinationen sind stückgeprüft, das schlagfeste Gehäuse ist aus hochwertigem Kunststoff in der Farbe grau, ähnlich RAL 7035. 2 Jahre Gewährleistung

Bestückung:

- 4x Schutzkontaktsteckdose 16A 230V IP54 schwarz
- 2x CEE-Steckdose 16A 400V 5p 6h IP54 gerade

Absicherung/Schutzmaßnahme:

- 2x C-Automat 16A 1p
- 1x C-Automat 16A 3p
- 1x FI-Schalter 40/0,03A 4p Typ A

Leitungseinführung/Anschlussmöglichkeit:

- 1x Kabelverschraubung M32 oben
- 1x Verschlusschraube M32 unten
- 1x Zählerklemmstein 5x25 mm²

DEHA-Nummer

7311747

Artikelnummer

3320-50-0005

EAN

4046725402275

Kennzeichnung

**IP
54**

CEE-Box 16-2, 2x CEE 16 A IP54/4x Schuko 16 A IP54

Allgemeine Daten

Merkmale	
Durchmesser Kabeleinführung	M32
Höhe	370 mm
Breite	240 mm
Tiefe	172 mm
Einspeisung/Anschlussmöglichkeit	2 Leitungen (Ringleitung/zum Durchschleifen)
Fehlerstrom-Typ	A
Farbe	grau
Werkstoff des Gehäuses	Kunststoff
Kontaktmaterial	CuZn
Oberflächenbehandlung der Kontakte	unbehandelt
CEE-Steckdose - 16 A	2x16A5p400V
Anzahl der SCHUKO-Steckdosen	4
FI-Schutzschalter	FI mit IFN 0,03 A (Standard)
Anzahl der Leitungsschutzschalter	3
Absicherung	LS-Schalter
Schutzart (IP)	IP54
Handhabung	Wandmontage


Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
7311747	CEE-BOX 16-2	3320-50-0005	4046725402275	1 Stück



CEE-Box 16-2, 2x CEE 16 A IP54/4x Schuko 16 A IP54



4 046725 402275

Performance features

The RED CEE-BOX 16-2 socket combination for fixed wall mounting is fully assembled and wired ready for connection. The RED CEE-BOX is designed for use in environments with a protection rating of up to IP54.

Thanks to professional wiring with high-quality circuit breakers, we can guarantee increased safety in accordance with DIN EN 61439. The circuit breakers are installed under a transparent and impact-resistant operating cover. The sockets are made of impact-resistant polyamide.

All socket combinations are individually tested, and the impact-resistant housing is made of high-quality plastic in gray, similar to RAL 7035. 2-year warranty.

Equipment:

- 4x 16A 230V IP54 black earthed socket outlets
- 2x 16A 400V 5-pin 6h IP54 straight CEE socket outlets

Protection/Protection measures:

- 2x 16A 1-pin C-circuit breakers
- 1x 16A 3-pin C-circuit breaker
- 1x 40/0.03A 4-pin residual current device Type A

Cable entry/Connection options:

- 1x M32 cable gland at the top
- 1x M32 screw plug at the bottom
- 1x 5x25 mm² meter terminal block

DEHA number

7311747

Item number

3320-50-0005

EAN

4046725402275

label

**IP
54**

CEE-Box 16-2, 2x CEE 16 A IP54/4x Schuko 16 A IP54

General Data

Features	
Cable entry diameter	M32
Height	370 mm
Width	240 mm
Depth	172 mm
Power supply/connection possibility	2 cables (ring line)
Leakage current type	A
Colour	Grey
Material housing	Plastic
Contact material	CuZn
Surface finish contacts	Untreated
CEE socket outlet 16 A	2x16A5p400V
Number of socket outlets with protective contact	4
Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)
Number of miniature circuit breakers	3
Protection	Over current switch
Degree of protection (IP)	IP54
Handling	Wall mounting

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
7311747	CEE-BOX 16-2	3320-50-0005	4046725402275	1 Piece