Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Gummi-Schuko-Stecker, IP44

4 046725 402503

Leistungsmerkmale

Der RED Gummi Schuko-Stecker, wurde gemäß DIN 49441 – 2 gebaut. Dank der Schutzart von IP44 ist der Stecker spritzwassergeschützt.

Technische Daten

- Leiterquerschnitt der Anschlußleitung 0,75 bis 2,5mm²
- Anzahl der Pole 2 + PE
- Schutzkontakt Ausführung mit zwei Schutzkontaktsystemen
- Zugentlastung Druckstück mit 2 Schrauben
- Max. Drehmoment für Anschlußschrauben 0,4 Nm
- Max. Drehmoment für Zugentlastung 0,5 Nm
- Mantelabisolierlänge 75–80 mm
- Aderabisolierlänge 7 mm
- Material Steckergehäuse PP (Polypropylen)
- Material Steckerkappe TPE (Elastomer)

Allgemeine Hinweise

- Vor dem Zuklappen der Steckergehäuse den Festsitz der Leitungen in den Anschlußklemmen kontrollieren und darauf achten, dass keine Leitung zwischen den Gehäuseteilen eingeklemmt wird.
- Die Verschlußschraube von Gummikappe und Innenkäfig so weit anziehen, bis der Schraubenkopf in die Gummikappe eintaucht

DEHA-Nummer

7435734

Artikelnummer

2430-20-0001

EAN

4046725402503

Kennzeichnung

Gummi-Schuko-Stecker, IP44

Allgemeine Daten

Merkmale	
Anschlusstechnik	Schraubklemme
Polzahl	2
Nennspannung	250 V
Nennstrom	16 A
Farbe	schwarz
Werkstoff	Gummi
Werkstoffgüte	Thermoplast
Ausführung	Hybridstecker CEE 7/7 (Typ E/F)
Schutzart (IP)	IP44
Steckrichtung	gerade
Für „erschwerte Bedingungen“ (nach VDE)	ja

Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
7435734	RED Gummi Schuko-Stecker	2430-20-0001	4046725402503	20 Stück

Data Sheet

RED®

SIMPLY. CONVINCING.

Rubber Schuko plug, IP44

4 046725 402503

Performance features

The RED rubber Schuko plug is manufactured according to DIN 49441-2. Thanks to its IP44 protection rating, the plug is splash-proof.

Technical Specifications

- Conductor cross-section of the connecting cable: 0.75 to 2.5 mm²
- Number of poles: 2 + PE
- Protective contact: version with two protective contact systems
- Strain relief: pressure piece with 2 screws
- Max. torque for connecting screws: 0.4 Nm
- Max. torque for strain relief: 0.5 Nm
- Sheath stripping length: 75–80 mm
- Wire stripping length: 7 mm
- Connector housing material: PP (polypropylene)
- Connector cap material: TPE (elastomer)

General Information

• Before closing the connector housing, check that the cables are firmly seated in the terminals and ensure that no cables are trapped between the housing parts. • Tighten the locking screw of the rubber cap and inner cage until the screw head is immersed in the rubber cap

DEHA number

7435734

Item number

2430-20-0001

EAN

4046725402503

label

SIMPLY. CONVINCING.

Rubber Schuko plug, IP44

General Data

Features	
Connection system	Screwed terminal
Number of poles	2
Nominal voltage	250 V
Nominal current	16 A
Colour	Black
Material	Rubber
Material quality	Thermoplastic
Model	Hybridstecker CEE 7/7 (Typ E/F)
Degree of protection (IP)	IP44
Angle of plug	Straight
For “difficult conditions” (according to VDE)	yes

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
7435734	RED Gummi Schuko-Stecker	2430-20-0001	4046725402503	20 Piece