




## Gummi-Schuko-3-fach Hängekupplung, IP44



4 046725 402527

### Leistungsmerkmale

Die RED Gummi Schuko 3-fach Hängekupplung wurde gemäß DIN 49440-2-D gebaut.

### Technische Daten

- Leiterquerschnitt der Anschlußleitung 0,75 bis 2,5mm<sup>2</sup>
- Anzahl der Pole: 2 + PE
- Schutzkontakt Ausführung als Seitenschutzkontakt gemäß DIN 49440
- Zugentlastung Druckstück mit 2 Schrauben
- Gehäuse TPE (Elastomer)
- Schutzart: IP44
- Klemmenart Schraubklemme; wiederanschließbar
- Material Kontaktträger Thermoplast,
- Material Gehäuse Thermoplast, TPE (Elastomer)

### Allgemeine Hinweise

- mit Aufhängebügel
- geeignet für Leitungen bis H07 RN-F 3G2,5

### DEHA-Nummer

7435736

### Artikelnummer

2430-20-0003

### EAN

4046725402527

### Kennzeichnung


**IP  
44**

### Gummi-Schuko-3-fach Hängekupplung IP44

#### Allgemeine Daten

| Merkmale          |                                       |
|-------------------|---------------------------------------|
| Anschluss technik | Schraubklemme                         |
| Polzahl           | 2                                     |
| Nennspannung      | 250 V                                 |
| Nennstrom         | 16 A                                  |
| Farbe             | schwarz                               |
| Werkstoff         | Gummi                                 |
| Werkstoffgüte     | Thermoplast                           |
| Halogenfrei       | ja                                    |
| Ausführung        | Schutzkontaktkupplung CEE 7/3 (Typ F) |
| Schutzart (IP)    | IP44                                  |
| Steckrichtung     | gerade                                |


#### Produktabbildungen

#### Bestelldaten

| DEHA-Nr. | Typ                                   | Artikelnummer | EAN           | VPE      |
|----------|---------------------------------------|---------------|---------------|----------|
| 7435736  | RED Gummi Schuko 3-fach Hängekupplung | 2430-20-0003  | 4046725402527 | 20 Stück |



## Rubber Schuko 3-way hanging coupling IP44



4 046725 402527

### Performance features

The RED rubber Schuko triple hanging coupling is manufactured in accordance with DIN 49440-2-D.

### Technical Specifications

- Conductor cross-section of the connecting cable: 0.75 to 2.5 mm<sup>2</sup>
- Number of poles: 2 + PE
- Protective contact: Side protective contact in accordance with DIN 49440
- Strain relief: Pressure piece with 2 screws
- Housing: TPE (elastomer)
- Degree of protection: IP44
- Terminal type: Screw terminal; rewirable
- Contact carrier material: Thermoplastic
- Housing material: Thermoplastic, TPE (elastomer)

### General Information

- With hanging bracket
- Suitable for cables up to H07 RN-F 3G2.5

### DEHA number

7435736

### Item number

2430-20-0003

### EAN

4046725402527

### label


**IP  
44**

## Rubber Schuko 3-way hanging coupling IP44

## General Data

| Features                  |                                 |
|---------------------------|---------------------------------|
| Connection system         | Screwed terminal                |
| Number of poles           | 2                               |
| Nominal voltage           | 250 V                           |
| Nominal current           | 16 A                            |
| Colour                    | Black                           |
| Material                  | Rubber                          |
| Material quality          | Thermoplastic                   |
| Halogen free              | yes                             |
| Model                     | Coupler with protective contact |
| Degree of protection (IP) | IP44                            |
| Angle of plug             | Straight                        |

## Product pictures

## Order Data

| DEHA no | Type                                  | Item number  | EAN           | VPE      |
|---------|---------------------------------------|--------------|---------------|----------|
| 7435736 | RED Gummi Schuko 3-fach Hängekupplung | 2430-20-0003 | 4046725402527 | 20 Piece |