

4 046725 402299

Leistungsmerkmale

Die LED-Handleuchte PORTLUX[®] PRO mit Schalter und Ladestandanzeige besitzt einen Li-Polymer Akku, der mittels USB-C geladen werden kann. Diese universell einsetzbare Arbeitsleuchte ist ausgestattet mit einem abnehmbarem Magnetfuß (Nylon) sowie einem Aufhängehaken.

Dank des robusten Aluminium-Gehäuses besitzt die PORTLUX[®] PRO eine Schlagfestigkeit von IK07.

Technische Daten

- Front LED: 500 lm (Dimm 100/50 %) , 6000 K, CRI>80
- Top LED: 100 lm, 7200 K, CRI>70
- Inkl. USB-C Ladekabel
- Arbeitszeit: 100 % 500 lm ca. 2 Std.
- Ladezeit: ca. 3,5 Std
- Batterietyp Lithium-Polymer 3,7 V/1,9 Ah

DEHA-Nummer

7312674


Artikelnummer

5610-20-0014

EAN

4046725402299

Kennzeichnung

CRI
>70

IP
20


IK
07


Allgemeine Daten

Merkmale	
Länge	200 mm
Höhe/Tiefe	13,5 mm
Breite	34,7 mm
Bemessungslichtstrom nach IEC 62722-2-1	500 lm
Spannungsart	DC
Stromversorgung	Akku
Nennspannung	3,7 - 3,7 V
Lichtfarbe	weiß
Farbtemperatur	6000 - 7200 K
Farbwiedergabeindex CRI	70-79
Betriebsdauer mit Akku-/Batteriesatz	2 h
Leuchtmittel	LED nicht austauschbar
Mit Leuchtmittel	ja
Mit Schalter	ja
Mit Aufhängehaken	ja
Mit Halterung	ja
Schutzart (IP)	IP20
Schutzklasse	III
Geeignet für Leuchtmittellanzahl	2

Produktabbildungen**Bestelldaten**

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
7312674	PORTLUXX [®] PRO	5610-20-0014	4046725402299	1 Stück

LED handheld light PORTLUX[®] PRO

4 046725 402299

Performance features

The PORTLUX[®] PRO LED handheld light with switch and charge indicator features a Li-polymer battery that can be charged via USB-C. This universally applicable work light is equipped with a removable magnetic base (nylon) and a hanging hook. Thanks to its robust aluminum housing, the PORTLUX[®] PRO has an impact resistance of IK07.

Technical Specifications

- Front LED: 500 lm (dimnable 100/50%), 6000 K, CRI>80
- Top LED: 100 lm, 7200 K, CRI>70
- Includes USB-C charging cable
- Working time: 100% 500 lm approx. 2 hours
- Charging time: approx. 3.5 hours
- Battery type: Lithium-polymer 3.7 V/1.9 Ah

DEHA number

7312674

Item number

5610-20-0014

EAN

4046725402299

labelCRI
>70

2h →

→ 3,5h

IP
20IK
07

LED handheld light PORTLUX[®] PRO

General Data

Features	
Length	200 mm
Height/depth	13,5 mm
Width	34,7 mm
Rated luminous flux acc. IEC 62722-2-1	500 lm
Voltage type	DC
Current supply	Accu
Nominal voltage	3,7 - 3,7 V
Colour of light	White
Colour temperature	6000 - 7200 K
Colour rendering index CRI	70-79
Betriebsdauer mit Akku-/Batteriesatz	2 h
Lamp type	LED not exchangeable
With light source	yes
With switch	yes
With suspension hooks	yes
With holder	yes
Degree of protection (IP)	IP20
Protection class	III
Suitable for number of lamps	2

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
7312674	PORTLUX [®] PRO	5610-20-0014	4046725402299	1 Piece