


LED-Netzgerät 24 V DC, schaltbar

Article no. 17342000







Tondor

LED-Netzgerät 24 V DC, schaltbar, white, Rectangular. Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 120 W, Dimmable: No, Control: on/off.

Article data	
Article no.	17342000
GTIN	4255752521358
Short description	LED-Netzgerät 24 V DC, schaltbar
Material	Plastic
Colour	White
Shape	Rectangular
Length	253.2 mm
Width	42.5 mm
Hight	31 mm
Weight	0.411 kg
stamp	ENEC
Conformance	CE



LED-Netzgerät 24 V DC, schaltbar

Article no. 17342000

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	47 Hz
Frequency max	63 Hz
Protection class	
Degree of protection	IP20
Power min	6 W
Power max.	120 W
Output_ripple_current	2
Starting current	56,4 A, 272 μs
Suitable for emergency lighting	No
Power factor	0.95
max. no. lights on B16 A	7
Output voltage max	31.00 V
Control	on/off
Connection type-primary	Plug-in connection
Connection type-secondary	Plug clamp
Number of poles	2
Enviroment temprature (ta)	-20°C bis +50°C
Measure point (tc)	max. +85°C
Average nominal lifespan	50000 h
Output current	250 - 5.000 mA
Noise development	20 dB

Packing data	
Gross weight	0.435 kg
Length of packaging	260 mm
Packaging width	46 mm
Packaging hight	35 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.