


LED surface-mounted luminaire for machines



| | |
|-----------------------------------|--|
| Product-Nr. | 111010-54 |
| EAN: | 4260556627915 |
| Model: | LEANLED II Basic-Line Opal White |
| Order number: | 111010-54 |
| Model: | LEANLED II Basic-Line Opal White |
| Type: | LED surface-mounted luminaire for machines |
| Illuminant: | SMD LED |
| Power consumption: | 11,6 W |
| Lamp luminous flux: | 1785 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light distribution: | Direct |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >80 |
| Number of poles: | 3 |
| Connected load: | 24V DC ± 10% * |
| Power supply: | External |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP54 |
| Class of protection: | III |
| Glare control: | opal white |
| Beam angle (optics): | 120° |
| Operating temperature: | 0 °C - +45 °C (32 °F - 113 °F) |
| Lamps lifetime: | > 60.000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | Polycarbonat |
| Height [B] x Width [C]: | 31 mm x 26 mm (~1,22" x ~1,02") |
| Length [A]: | 520 mm (~20,47") |
| Weight (net): | 440 g (~16 oz) |
| Gross weight: | 500 g (~18 oz) |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA |
| Dimmable: | No |
| Mounting accessories: | Including swivel and fixed bracket |
| Made in: | Germany |
| Note: | In case of an undervoltage supply (< 24V DC), the luminous flux is reduced |
| cascadable: | No |