




## LED system light



|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Product-Nr.                | 155010-03                                                  |
| EAN:                       | 4260556627953                                              |
| Model:                     | SYSTEMLED EVO PIR - POWER Daylight White                   |
| Order number:              | 155010-03                                                  |
| Model:                     | SYSTEMLED EVO PIR - POWER Daylight White                   |
| Type:                      | LED system light                                           |
| Illuminant:                | SMD LED                                                    |
| Total output incl. driver: | ~21 W                                                      |
| Power consumption:         | ~18 W                                                      |
| Lamp luminous flux:        | 3250 lm                                                    |
| Lamp luminous efficiency:  | 184 lm/W                                                   |
| Light distribution:        | Direct                                                     |
| Light colour:              | 5700K 3-step MacAdam                                       |
| R9:                        | 90                                                         |
| Colour rendering (Ra):     | >90 (typ. 95)                                              |
| UGR:                       | <22                                                        |
| Dimming:                   | Via external control; On / Off via motion activation (PIR) |
| Connected load:            | 120-277V AC $\pm$ 10%, 50-60 Hz                            |
| Power supply:              | Integrated                                                 |
| Connection (connector):    | Wieland GST18                                              |
| Degree of protection:      | IP40                                                       |
| Class of protection:       | I                                                          |
| Glare control:             | Microprisms                                                |
| Beam angle (optics):       | 90°                                                        |
| Operating temperature:     | -10 °C - +50 °C (14 °F - 122 °F)                           |
| Storage temperature:       | -20 °C - +80 °C (-4 °F - 176 °F)                           |
| Lamps lifetime:            | > 100.000 h (L80/B10)                                      |
| Housing material:          | aluminum and PMMA                                          |
| Height [B] x Width [C]:    | 48 mm x 139 mm (~1,89" x ~5,47")                           |
| Length [A]:                | 472 mm (~18,58")                                           |
| Mounting:                  | T-nut, rear side (slot 8)                                  |
| Weight (net):              | 1500 g (~53 oz)                                            |
| Gross weight:              | 2080 g (~73 oz)                                            |
| Risk group (DIN EN 62471): | Free group                                                 |
| Markings:                  | CE, UKCA                                                   |
| Dimmable:                  | Optional via accessories                                   |
| Mounting accessories:      | Optional                                                   |
| Made in:                   | Germany                                                    |