




LED system light



Abstand d=100 cm

 $E_{\text{min}} = 1655 \text{ lux}$
 $E_{\text{max}} = 2027 \text{ lux}$
 $E_{\text{avg}} = 1149 \text{ lux}$


Product-Nr.	155410-04
EAN:	4260556628080
Model:	SYSTEMLED EVO PIR - ECO Daylight White
Order number:	155410-04
Model:	SYSTEMLED EVO PIR - ECO Daylight White
Type:	LED system light
Illuminant:	SMD LED
Total output incl. driver:	~51 W
Power consumption:	~46 W
Lamp luminous flux:	7960 lm
Lamp luminous efficiency:	173 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
R9:	90
Colour rendering (Ra):	>90 (typ. 95)
UGR:	<22
Dimming:	Via external control; On / Off via motion activation (PIR)
Connected load:	120-277V AC $\pm$ 10%, 50-60 Hz
Power supply:	Integrated
Connection (connector):	Wieland GST18
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	90°
Operating temperature:	-10 °C - +50 °C (14 °F - 122 °F)
Storage temperature:	-20 °C - +80 °C (-4 °F - 176 °F)
Lamps lifetime:	> 100.000 h (L80/B10)
Housing material:	aluminum and PMMA
Height [B] x Width [C]:	48 mm x 139 mm (~1,89" x ~5,47")
Length [A]:	1782 mm (~70,16")
Mounting:	T-nut, rear side (slot 8)
Weight (net):	4700 g (~166 oz)
Gross weight:	6580 g (~232 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Dimmable:	Optional via accessories
Mounting accessories:	Optional
Made in:	Germany