

assembly aid enclosed

SW15
width across
flat: 15

A (2:1)
contact face acc. to
IEC 61076-2-101

SW18
width across
flat: 18

M12x1

M16x1,5

SW19
width across
flat: 19

pin	colour
1	yellow
2	white
3	orange
4	blue

complete length when assembled app. 42

panel
thickness

Panel cut out
(1:1)



recommended torque of counter nut: 2Nm
order contacts separately

min.2 - max.5

∅16,3±0,2

14,3±0,2

cable∅			wire gauge	part-no.
5,7 - 6,9mm	6,5 - 7,7mm	7,5 - 8,8mm		
sealing			AWG 26-22	09 67 000 5476
A	B	C	AWG 24-20	09 67 000 8476
			AWG 22-18	09 67 000 3476



All Dimensions in mm
Original Size DIN A4

Scale
1:1

Free size tol.

Ref.

Sub.



All rights reserved
Department EL PD

Created by
406551

Inspected by
farcasiu

Standardisation

Date
14-Feb-2025

State
40 - Released

Title

M12 PFT Slim Design female D-cod 4-pol

Doc-Key / ECM-Nr.
DS00197331

HARTING
D-32339 Espelkamp

Type
TB

Design Number
DS00197331

SAP Mat. Number
21038812425

Rev.
N

Page
1/1